EverCharge

240kW Power Cabinet With Aircooled Dispenser









		240kW Power Cabinet	Dual Handle Dispenser with Cable Management
Power Input	Input Rating	408-530Vac, 50/60 Hz, L1, L2, L3, N, PE	AC:432-528Vac (From power cabinet) DC:150-1000Vdc
	Power Factor	≥0.98	
Power Output	DC Output Voltage	150-1000Vdc	
	Output Rating	240kW (4 outputs)	80kW@400VDC and 160kW@800V per handle max
	Max Output Current	800A@300V	Handle A/B 200A
	Connector Type	N/A	Dual CCS1 or NACS
User Interface and Control	Display	LED Status Lights	10.4" LCD Touch Panel
Environmental	Operating Temperature	-30°C-55°C (>50°C derating)	
Mechanical	Cable Length	N/A	16.4 FT
	Ingress Protection	NEMA 3R/IK10	
	Dimensions	80.70 in x 41.33 in x 29.52 in	78.7in x 37in x 17.71in
	Net Weight	882 LBS	575 LBS
Regulation	Safety and Compliance	TUV and cTUVus listed; complies with UL 2202 and UL 2231	
	Certificate	UL2202, UL2231-1/-2, FCC part 15B, Energy Star	
Connectivity	Network	Ethernet	4G + Mesh Networking