

---If clients are missing from Find Client results, those client may be missing a required record in the cw\_client\_custom table for that provider. To add those records for client missing in Find Client results, run the following query---

```
DECLARE @customColumnStr nvarchar(max)
DECLARE @columnName nvarchar(50)

DECLARE abc CURSOR FOR (SELECT col.name as columnName
from sys.tables as tab
inner join sys.columns as col
on tab.object_id = col.object_id
where tab.name = 'cw_client_custom'
and (col.name like 'f%' or col.name = 'cst_sb_date'))

SET @customColumnStr =
OPEN abc FETCH Next FROM abc INTO @columnName
WHILE @@FETCH_STATUS = 0
BEGIN
IF (len(@customColumnStr) > 0) SET @customColumnStr = @customColumnStr + ','
SET @customColumnStr = @customColumnStr + @columnName
FETCH Next FROM abc INTO @columnName
End
CLOSE abc
DEALLOCATE abc

DECLARE @client uniqueidentifier
DECLARE @domain uniqueidentifier
DECLARE @otherCustomRecordPK uniqueidentifier
DECLARE @insertStatement nvarchar(max)

DECLARE clients CURSOR FOR (SELECT map_cl_cln_fk, map_cl_dmn_fk
                           FROM cw_map_client_provider
                           WHERE NOT EXISTS(SELECT cln_cs_pk FROM
cw_client_custom
                           WHERE
cln_cs_cln_fk = map_cl_cln_fk
                           AND
cln_cs_dmn_fk = map_cl_dmn_fk))

OPEN clients FETCH Next FROM clients INTO @client, @domain
WHILE @@FETCH_STATUS = 0
BEGIN
SET @otherCustomRecordPK = (SELECT TOP 1 cln_cs_pk FROM cw_client_custom WHERE
cln_cs_cln_fk = @client);

IF @otherCustomRecordPK IS NULL
BEGIN
SET @insertStatement = 'INSERT INTO cw_client_custom(cln_cs_pk, cln_cs_cln_fk,
cln_cs_dmn_fk, cln_cs_last_updated)';
SET @insertStatement = @insertStatement + 'VALUES(NewID(), ' + "" + Convert(Nvarchar(36),
@client) + "" + ',';
SET @insertStatement = @insertStatement + "" + Convert(Nvarchar(36), @domain) + "" + ',
```

```
GetDate());
EXECUTE sp_executesql @insertStatement;
END
ELSE
BEGIN
SET @insertStatement = 'INSERT INTO cw_client_custom(cln_cs_pk, cln_cs_cln_fk,
cln_cs_dmn_fk, cln_cs_last_updated, ';
SET @insertStatement = @insertStatement + @customColumnStr + ')';
SET @insertStatement = @insertStatement + '(SELECT NewID(), ' + ""'' + Convert(Nvarchar(36),
@client) + ""'' + ', ';
SET @insertStatement = @insertStatement + ""'' + Convert(Nvarchar(36), @domain) + ""'' + ',
GetDate(), ';
SET @insertStatement = @insertStatement + @customColumnStr;
SET @insertStatement = @insertStatement + ' FROM cw_client_custom WHERE cln_cs_pk = '
SET @insertStatement = @insertStatement + ""'' + Convert(Nvarchar(36),
@otherCustomRecordPK) + ""'' + ')';
EXECUTE sp_executesql @insertStatement;
END

FETCH Next FROM clients INTO @client, @domain
End
CLOSE clients
DEALLOCATE clients
```