

Custom Report Field Descriptions

Purpose	Define the custom report fields and filter parameters listed in the supplied Custom Report Columns workbook, organized by report type.
Who should use this	CAREWare administrators, data managers, report writers, quality staff, and support users who create, validate, or troubleshoot custom reports.
Use this guide when	Selecting report fields, defining report filters and subfilters, interpreting report output, or checking the database record represented by a field.
Source Basis	CAREWare Creating Custom Reports and Custom Report Run Report
Main warning	The report type determines the available fields and filters. Similar field names can produce different results when the critical date, key date, provider-sharing settings, funding source, code system, or subfilter criteria differ.

Quick path

Reports > Custom Reports Menu > Manage/Run Custom Reports > select a report > Field Selection or Report Filter

Before you use this reference

- Choose the report type first; it controls the record represented by each row and which field and filter options are available.
- Use Date From and Date Through with the report type's critical date. Some history, first, last, previous, and as-of fields intentionally evaluate records outside Date From through the selected reference date.
- For multi-provider reports, confirm [provider permissions](#) and [data sharing](#) settings before comparing counts.
- Include client identifiers, source dates, provider, status, code, and funding fields when validating a calculated result.

Important

A field can display a value, while a filter limits which clients or records are included. Subfilter fields supply additional parameters—such as a service category, code, date span, provider, threshold, or sequence rule—to the parent filter.

Tip

Demographics reports normally produce one row per client. Most other report types produce one row per record, so one client may appear on several rows. Confirm the row basis before interpreting totals or client counts.

Description conventions

Term	Description
Displays	A value read from the primary record or resolved from a linked reference record.
Indicates	A Yes/No-style condition calculated from a stored flag or the existence of qualifying records.
Returns	A derived, selected, first, last, current, highest, lowest, or as-of result.
Counts / totals	An aggregate of qualifying database records or numeric values; the description states when the result is client-level or record-level.
Internal identifier	A database key intended for reconciliation, joins, or troubleshooting rather than a user-facing label.

Report Type

Report Type	Row / Database Basis	Critical Date or Date Behavior
ADAP Enrollment History	One row represents an ADAP enrollment or disenrollment event. Statuses and disenrollment reasons are resolved from linked reference records.	ADAP Enrollment History Date
Case Notes	One row represents a client case note, with the employee and provider relationships used to identify the author and domain.	Case Note Date
Child	One row represents a relationship link and displays attributes from the client identified as the child or dependent side of that link.	Relations behavior; Service Date
Counseling and Testing	One row represents a counseling and testing encounter, including counseling, HIV testing, notification, and provider values.	HIV Test Date
Custom Forms	One row represents a saved custom form record and may include values from a service linked to that form.	Form Date or Master Date if enabled
Custom Subform	One row represents a custom subform entry. Dynamic field values follow the custom control definition, data type, and active value list.	Custom Subform Date
Demographics	One row represents one client. Direct client values are combined with calculated results drawn from related clinical, service, enrollment, eligibility, insurance, referral, and custom records.	No single intrinsic critical date; date-span, key-date, and annual-review settings control many calculated fields
Diagnosis	One row represents a diagnosis record. Diagnosis labels, assessments, statuses, and code descriptions may be resolved from linked reference and coding records.	Diagnosis Date
Drug Service	One row represents an ADAP drug service or dispensed-drug transaction and may join formulary, NDC, generic drug, funding, payment, and dispenser details.	Drug Service Date
Eligibility	One row represents an eligibility determination, linked to the client, provider domain, funding source, and eligibility status.	Eligibility Date
Immunization	One row represents an immunization record, with vaccine definitions and code mappings used to resolve names, CVX values, and related attributes.	Vaccine Date
Insurance Assessment	One row represents an insurance assessment. Coverage flags, primary coverage, codes, and descriptive values are read from the assessment and linked insurance reference records.	Insurance Assessment Date
Lab	One row represents a lab test record. Test definitions, assays, result values, code mappings, data source, status, and provider may be joined to the test record.	Lab Date
Medication	One row represents a client medication record, linked to medication definitions, frequency, indication, prophylaxis, coding, form, and provider values.	Medication Start Date and Stop Date

Report Type	Row / Database Basis	Critical Date or Date Behavior
Parent	One row represents a relationship link and displays attributes from the client identified as the parent or index side of that link.	Relations behavior; Service Date
Poverty Level Assessment	One row represents a poverty level assessment containing household income, household size, individual income, and the calculated federal poverty level.	Poverty Level Assessment Date
Pregnancy History	One row represents a pregnancy history record, including conception, prenatal care, antiretroviral use, outcome, delivery, newborn status, and provider values.	Conception Date, generally the estimated conception date
Referrals	One row represents a referral. Provider, service category, definition, class, type, status, code, user, and received-service relationships may supply display values.	Referral Date
Relations	One row represents a relationship link between an index client and a dependent client, with the relationship type and related-client attributes resolved through linked records.	Service Date
ROI Agreement	One row represents a release-of-information agreement, including its active period, provider domain, and sharing type.	ROI Start Date and ROI End Date
Screening	One row represents a screening test record. Screening definitions, actions, results, scores, status, code mappings, data source, and provider may be joined to the test record.	Screening Date
Screening Lab	One row represents a screening-lab test record. Test definitions, qualitative or titer results, treatment, STI action, code mappings, source, and provider may supply report values.	Screening Lab Date
Service	One row represents a service record, linked to subservice, service category, contract, sponsor, funding, provider, code, tag, billing, and user records.	Service Date
Service Receipts	One row represents a receipt linked to a service record, so receipt values can be reported with the service, contract, funding, provider, billing, and subservice details.	Receipt Date
Vital Signs	One row represents a vital-sign encounter containing date, height, weight, pulse, blood pressure, temperature, provider, and calculated BMI values.	Vitals Date

ADAP Enrollment History

One row represents an ADAP enrollment or disenrollment event. Statuses and disenrollment reasons are resolved from linked reference records.

Date behavior: ADAP Enrollment History Date.

Field Name	Description
ADAP Enrollment History Date	Displays the date of the client's ADAP enrollment or disenrollment event. This is the critical date used to place ADAP enrollment-history rows within Date From and Date Through.

Field Name	Description
ADAP Enrollment History Status	Displays the enrollment status assigned to the ADAP history event, resolved from the ADAP enrollment-status reference values.
ADAP History Disenroll Reason	Displays the standard ADAP disenrollment reason linked to a disenrollment event, using the configured disenrollment-reason reference value.
ADAP Other Disenroll Reason	Displays the locally maintained other disenrollment reason linked to the ADAP enrollment-history event.

Case Notes

One row represents a client case note, with the employee and provider relationships used to identify the author and domain.

Date behavior: Case Note Date.

Field Name	Description
Case Note Author	Displays the employee associated with the case note, using the employee link stored on the case-note record.
Case Note Comment	Displays the short comment recorded separately from the full case-note narrative.
Case Note Date	Displays the date and time assigned to the case note. This is the critical date used to include case-note rows within the report date span.
Case Note Date Created	Displays the database timestamp recorded when the case-note record was created, which can differ from the case-note date used for reporting.
Case Notes	Displays the full narrative text entered for the client case note.
Case Notes Author First Name	Displays the first name of the employee linked as the case-note author.
Case Notes Author Last Name	Displays the last name of the employee linked as the case-note author.

Child

One row represents a relationship link and displays attributes from the client identified as the child or dependent side of that link.

Date behavior: Relations behavior; Service Date is identified for the Relations report type in CAREWare guidance.

Field Name	Description
Relation AIDS diagnosis date	Displays the AIDS diagnosis date for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation date case closed	Displays the date the related client's case or enrollment was closed for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation date of birth	Displays the date of birth for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation date of death	Displays the date of death for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation enroll date	Displays the provider enrollment date for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.

Field Name	Description
Relation enroll status	Displays the provider enrollment status for the client on the child or dependent side of the relationship, resolved from the applicable client or provider-enrollment reference value.
Relation eURN	Displays the encrypted or extended unique record number for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation first name	Displays the first name for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation gender	Displays the gender for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation HIV diag date	Displays the HIV diagnosis date for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation last name	Displays the last name for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation middle name	Displays the middle name for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation type	Displays the relationship type that links the index client and dependent client, resolved from the relationship reference values.
Relation URN	Displays the unique record number for the client on the child or dependent side of the relationship by joining the relationship link to that client's record.
Relation vital status	Displays the vital status for the client on the child or dependent side of the relationship, resolved from the applicable client or provider-enrollment reference value.

Counseling and Testing

One row represents a counseling and testing encounter, including counseling, HIV testing, notification, and provider values.

Date behavior: HIV Test Date.

Field Name	Description
C&T Provider	Displays the provider domain associated with the counseling and testing encounter.
Comment	Displays the additional comment entered on the counseling and testing record.
HIV Result	Displays the HIV test result recorded for the encounter, resolved from the HIV test-result reference values.
HIV test date	Displays the date of the HIV test. This is the critical date used to include counseling and testing rows within the report date span.
HIV Tested	Indicates whether the client was recorded as HIV tested for the encounter, using the configured Yes/No/Unknown/Not Applicable value set.
Notified of HIV test result	Indicates whether the client was notified of the HIV test result for the encounter.
Partner notification offered	Indicates whether partner-notification services were offered during the encounter.

Field Name	Description
Post-test counsel date	Displays the date post-test counseling occurred for the encounter.
Post-test counseled	Indicates whether post-test counseling was provided, using the configured Yes/No/Unknown/Not Applicable value set.
Pre test counsel date	Displays the date pre-test counseling occurred for the encounter.
Pre-test counsel	Indicates whether pre-test counseling was provided, using the configured Yes/No/Unknown/Not Applicable value set.
Reason not counseled	Displays the reason recorded when post-test counseling was not provided.

Custom Forms

One row represents a saved custom form record and may include values from a service linked to that form.

Date behavior: Form Date or linked Service Date, depending on the selected field and report design.

Field Name	Description
Created By	Displays the user or employee associated with creating the custom form record.
Form Date	Displays the date assigned to the custom form record.
Form Employee	Displays the employee linked to the custom form record.
Form Label	Displays the label configured for the custom form.
Form Name	Displays the configured name of the custom form design.
Form PK	Displays the internal unique identifier for the saved custom form record; use it for technical reconciliation or joins.
Form Provider	Displays the provider domain associated with the custom form record.
Form User	Displays the user associated with the saved custom form record.
Last Updated By	Displays the user associated with the most recent update to the custom form record.
Service Date Created	Displays the database timestamp recorded when the linked service record was created.
Service Primary Key	Displays the internal unique identifier for the service linked to the custom form record.
Service User	Displays the user name stored with the service linked to the custom form record.
Srv Cat PK	Displays the internal key for the service category linked to the form's service record.
Srv Category	Displays the service category linked to the form's service record.
Srv Contract	Displays the contract linked to the form's service record.
Srv Date	Displays the date of the service linked to the custom form record.
Srv Funding	Displays the funding source linked to the form's service record.
Srv Long Name	Displays the long name of the linked service or subservice.

Field Name	Description
Srv Price	Displays the unit price recorded for the linked service.
Srv Qty	Displays the quantity or units recorded for the linked service.
Srv RW Funded	Indicates whether the linked service is Ryan White funded.
Srv Short Name	Displays the short name of the linked service or subservice.
Srv Total	Displays the stored total amount for the linked service.
Srv Total Recd	Displays the total amount received from sources associated with the linked service.
Subservice Tags	Displays the tags assigned to the subservice linked to the form's service record.
Tag	Displays the selected tag associated with the custom form or linked service configuration.

Custom Subform

One row represents a custom subform entry. Dynamic field values follow the custom control definition, data type, and active value list.

Date behavior: Custom Subform Date.

Field Name	Description
Adherence to Cotrimoxazole (Test New Subform)	Displays the value entered for the custom field "Adherence to Cotrimoxazole" on the "Test New Subform" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary Comment (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary Comment" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary Date of Birth (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary Date of Birth" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary Ethnicity Hispanic (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary Ethnicity Hispanic" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary Gender (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary Gender" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary HIV Status Positive (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary HIV Status Positive" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary Name (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary Name" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.
Beneficiary Race (HOPWA Beneficiaries)	Displays the value entered for the custom field "Beneficiary Race" on the "HOPWA Beneficiaries" custom subform. The value's data type, validation, and allowed choices follow the custom control definition.

Field Name	Description
Cognitive function assessed? (Test New Subform)	Displays the value entered for the custom field “Cognitive function assessed?” on the “Test New Subform” custom subform. The value’s data type, validation, and allowed choices follow the custom control definition.
HOPWA Beneficiary Age Category	Returns the HOPWA beneficiary age category derived from the beneficiary date of birth and the reporting reference date.
New Subform Drop Down List (New Subform Tab)	Displays the value entered for the custom field “New Subform Drop Down List” on the “New Subform Tab” custom subform. The value’s data type, validation, and allowed choices follow the custom control definition.

Demographics

One row represents one client. Direct client values are combined with calculated results drawn from related clinical, service, enrollment, eligibility, insurance, referral, and custom records.

Date behavior: No single intrinsic critical date; date-span, key-date, and annual-review settings control many calculated fields.

Field Name	Description
Hepatitis C Screening	Returns the client-level “Hepatitis C Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
HIV risk counseling	Returns the client-level hiv risk counseling, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
RW-funded visits by service category (RDR)	Returns the number of qualifying service or appointment records represented by “Ryan White-funded visits by service category (RDR)”, after applying service-category, subservice, funding, and interval criteria.
2nd To Last Lab Date	Returns the second most recent qualifying lab date through the report Date Through, after applying the selected test and subfilter criteria.
2nd to Last Lab Value	Returns the second most recent qualifying lab value through the report Date Through, after applying the selected test and subfilter criteria.
2nd To Last Qualitative Test Date	Returns the second most recent qualifying qualitative test date through the report Date Through, after applying the selected test and subfilter criteria.
2nd To Last Qualitative Value	Returns the second most recent qualifying qualitative value through the report Date Through, after applying the selected test and subfilter criteria.
ADAP Application Date	Returns the adap application date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
ADAP Disenroll Reason	Returns the client-level adap disenroll reason, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
ADAP Enrolled In Period	Returns the client-level “ADAP Enrolled In Period” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
ADAP enrollment status	Returns the client-level adap enrollment status, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
ADAP Enrollment Status By Date	Returns the latest applicable adap enrollment status on or before the configured key date or report Date Through.

Field Name	Description
ADAP First Enrollment Date	Returns the adap first enrollment date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
ADAP First Enrollment Date Not Disenrolled	Returns the adap first enrollment date not disenrolled from the client record or the qualifying related record selected by the field's date and subfilter criteria.
ADAP First Enrollment Status	Returns the client-level adap first enrollment status, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
ADAP Formatted NDC	Returns the client-level "ADAP Formatted NDC" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
ADAP Is Last Disenrolled By Reason Before Date	Returns the adap is last disenrolled by reason before date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
ADAP Last Enrl Date Not Disenrolled	Returns the adap last enrollment date not disenrolled from the client record or the qualifying related record selected by the field's date and subfilter criteria.
ADAP Last Enrollment Date	Returns the adap last enrollment date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
ADAP Last Enrollment Status	Returns the client-level adap last enrollment status, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
ADAP Legacy Date Closed	Returns the adap legacy date closed from the client record or the qualifying related record selected by the field's date and subfilter criteria.
ADAP Premium Months	Returns the client-level "ADAP Premium Months" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Address	Displays the street address recorded on the client record.
Adh. Prob. Addressed?	Indicates whether the client satisfies the "Adh. Prob. Addressed" condition based on qualifying client or related records.
Adh. Prob. Identified?	Indicates whether the client satisfies the "Adh. Prob. Identified" condition based on qualifying client or related records.
Adh. Quan. Assessed?	Indicates whether the client satisfies the "Adh. quantitative Assessed" condition based on qualifying client or related records.
Adherence Assessment	Returns the client-level "Adherence Assessment" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Adherence Rate	Calculates the percentage or rate represented by "Adherence Rate" from the qualifying numerator and denominator values defined by the field and its date criteria.
ADR Client In Period	Returns the client-level "ADR Client In Period" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.

Field Name	Description
ADR Gender	Returns the client-level “ADR Gender” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
ADR Has Med With No Days	Returns the client-level “ADR Has medication With No Days” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
ADR Hispanic	Returns the client-level “ADR Hispanic” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
ADR Poverty Level	Returns the client-level “ADR Poverty Level” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
ADR Pregnant in Period	Returns the client-level “ADR pregnancynant in Period” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Age	Returns the client’s age calculated from date of birth and the report’s reference date.
Age at Begin Date	Returns the client’s age on the report Date From value.
Age At Date	Returns the client’s age on the configured key date.
Age at Enrollment	Returns the client’s age on the applicable provider enrollment date.
Age In Months	Returns the client’s age in completed months on the report’s reference date.
AgeGroup	Returns the age category determined by the field’s configured number-format ranges.
AIDS Clients on HAART	Returns the client-level “AIDS Clients on HAART” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
AIDS diagnosis date estimated	Indicates whether the AIDS diagnosis date on the client record is marked as estimated.
All Disbursements Have Pickups	Returns the client-level “All Disbursements Have Pickups” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Allergies	Displays the medication-allergy text recorded on the client record.
Alt Phone 1 Type	Displays the type assigned to the client’s first alternate phone number.
Alt Phone 2 Type	Displays the type assigned to the client’s second alternate phone number.
Alt. Phone 1	Displays the client’s first alternate phone number.
Alt. Phone 2	Displays the client’s second alternate phone number.
American Indian or Alaska Native	Indicates whether American Indian or Alaska Native is selected for the client’s race.
Annual Mental Health Screening	Returns the client-level “Annual Mental Health Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.

Field Name	Description
Annual Review Year	Returns the client-level “Annual Review Year” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Annual Substance Abuse Screening	Returns the client-level “Annual Substance Abuse Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Another Hispanic, Latino/a Or Spanish origin	Returns the client-level “Another Hispanic, Latino/a Or Spanish origin” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Anxiety Screen?	Indicates whether the client satisfies the “Anxiety Screen” condition based on qualifying client or related records.
Appetite Assessment?	Indicates whether the client satisfies the “Appetite Assessment” condition based on qualifying client or related records.
ART date stopped by date	Returns the art date stopped by date from the client record or the qualifying related record selected by the field’s date and subfilter criteria. As of the configured key date or report date through.
ART first prescribed date	Returns the art first prescribed date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
ART medications during pregnancy	Returns the client-level art medications during pregnancy, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
ART taken during pregnancy (RDR)	Returns the client-level “ART taken during pregnancy (RDR)” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
ART taken in pregnancy by date	Returns the art taken in pregnancy by date from the client record or the qualifying related record selected by the field’s date and subfilter criteria. As of the configured key date or report date through.
Asian Indian	Indicates whether Asian Indian is selected for the client’s Asian subgroup.
Association Plan	Returns the client-level “Association Plan” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Begin Date	Displays the Date From parameter used to run the custom report.
Billing Dgn Date	Returns the billing diagnosis date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
Billing Provider N5	Returns the client-level billing provider n5, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Billing Provider NPI	Returns the client-level billing provider np, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Birth Year	Returns the calendar year from the client’s date of birth.
Black or Afr American	Indicates whether Black or African American is selected for the client’s race.

Field Name	Description
Category Visits In Span By Funding	Returns the number of qualifying service or appointment records represented by “Category Visits In Span By Funding” within the configured Date From and Date Through span, after applying service-category, subservice, funding, and interval criteria.
CD4 Count from first ART in Span	Returns the number of qualifying records or items represented by “CD4 Count from first ART in Span” within the configured Date From and Date Through span. The count is record-based unless the field explicitly defines unduplicated clients.
CD4<200 with PCP proph CQM 2025 Edited	Returns the client-level “CD4<200 with PCP proph CQM 2025 Edited” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
CD4<200 with PCP prophylaxis	Returns the client-level cd4<200 with pcp prophylaxis selected or calculated from qualifying vital-sign, lab, or screening records.
Cervical Cancer Screening	Returns the client-level “Cervical Cancer Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Cervical Cancer Screening Copy _6cf6	Returns the client-level “Cervical Cancer Screening Copy _6cf6” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Change in Screening Score for period	Calculates the difference represented by “Change in Screening Score for period” between the selected earlier and later qualifying values.
Chinese	Indicates whether Chinese is selected for the client’s Asian subgroup.
Chlamydia Screening	Returns the client-level “Chlamydia Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
City	Displays the client’s city of residence.
Client Date Created	Displays the database timestamp recorded when the client record was created.
Client ID	Displays the provider or application client identifier configured for the client.
Client is Pregnant	Returns the client-level “Client is pregnancynant” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Client On ART	Returns the client-level “Client On ART” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Client On ART After Span	Returns the client-level “Client On ART After Span” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Client On ART During Span	Returns the client-level “Client On ART During Span” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Client pregnant at enrollment	Returns the client-level “Client pregnant at enrollment” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.

Field Name	Description
Client User	Displays the user identifier associated with the client record or client portal account.
Client's Bar Code	Displays the barcode value associated with the client record.
Clients with visit in last 4 months	Returns the client-level "Clients with visit in last 4 months" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Clinical data shared by client	Indicates whether client-level clinical data sharing is enabled for the client.
Cog. Func. Assessed?	Indicates whether the client satisfies the "Cog. Func. Assessed" condition based on qualifying client or related records.
Completed Hep A vaccine series	Indicates whether the client satisfies the "Completed Hep A vaccine series" condition based on qualifying client or related records.
Completed Hep B vaccine series	Indicates whether the client satisfies the "Completed Hep B vaccine series" condition based on qualifying client or related records.
Counseled about HIV risks	Indicates whether the client satisfies the "Counseled about HIV risks" condition based on qualifying client or related records.
Counseled about HIV risks by	Indicates whether the client satisfies the "Counseled about HIV risks by" condition based on qualifying client or related records.
County of residence	Displays the county linked to the client's address.
Cuban	Indicates whether Cuban is selected for the client's Hispanic subgroup.
Current Antiretrovirals	Returns the active or most recent antiretrovirals as of the report's reference date, using related medication or regimen records.
Current ARV Abbreviation	Returns the active or most recent arv abbreviation as of the report's reference date, using related medication or regimen records.
Current ARV Hrt Classes	Returns the active or most recent arv art classes as of the report's reference date, using related medication or regimen records.
Current Regimen	Returns the active or most recent regimen as of the report's reference date, using related medication or regimen records.
Current Regimen Line	Returns the active or most recent regimen line as of the report's reference date, using related medication or regimen records.
Current Regimen Months	Returns the active or most recent regimen months as of the report's reference date, using related medication or regimen records.
Current Regimen Start Date	Returns the active or most recent regimen start date as of the report's reference date, using related medication or regimen records.
Date ARV med first started in date span	Returns the date arv med first started in date span from the client record or the qualifying related record selected by the field's date and subfilter criteria. Within the configured date from and date through span.
Date client closed out services	Returns the date client closed out services from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date determined ready for antiretrovirals	Returns the date determined ready for antiretrovirals from the client record or the qualifying related record selected by the field's date and subfilter criteria.

Field Name	Description
Date Diff	Calculates the number of days between the two dates selected by the field and its subfilter settings.
Date First HIVQUAL Referral Made	Returns the date first hivqual referral made from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date First HIVQUAL Referral Received	Returns the date first hivqual referral received from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date First HIVQUAL Referral Received after PAP smear abnormal result	Returns the date first hivqual referral received after pap smear abnormal result from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date First Referral Made	Returns the date first referral made from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date First Referral Received	Returns the date first referral received from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date last antiretroviral stopped	Returns the date last antiretroviral stopped from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date Last Referral Made	Returns the date last referral made from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date Last Referral Received	Returns the date last referral received from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date Of Last Insurance Assessment In Span	Returns the most recent qualifying insurance assessment in span within the configured Date From and Date Through span.
Date of ADAP enrollment	Returns the date of adap enrollment from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date of AIDS diagnosis	Displays the AIDS diagnosis date recorded on the client record.
Date of birth	Displays the client's date of birth.
Date Of Death	Displays the date of death recorded on the client record.
Date of first ADAP service	Returns the earliest qualifying adap service from the client's available history through the report Date Through.
Date of first ARV medication ever	Returns the earliest qualifying arv medication ever from the client's available history through the report Date Through.
Date of First HIVQUAL service	Returns the earliest qualifying hivqual service from the client's available history through the report Date Through.
Date Of First Insurance Assessment In Span	Returns the earliest qualifying insurance assessment in span within the configured Date From and Date Through span.
Date Of First Poverty Level In Span	Returns the earliest qualifying poverty level in span within the configured Date From and Date Through span.
Date of first service	Returns the earliest qualifying service from the client's available history through the report Date Through.
Date of first service category in date span	Returns the earliest qualifying service category in date span within the configured Date From and Date Through span.

Field Name	Description
Date of First Subservice	Returns the earliest qualifying subservice from the client's available history through the report Date Through.
Date of first vaccination	Returns the earliest qualifying vaccination from the client's available history through the report Date Through.
Date of HIV diagnosis	Displays the HIV diagnosis date recorded on the client record.
Date of last ADAP service	Returns the most recent qualifying adap service from the client's available history through the report Date Through.
Date of Last ARV Med Change	Returns the most recent qualifying arv medication change from the client's available history through the report Date Through.
Date of Last ARV Med Stop	Returns the most recent qualifying arv medication stop from the client's available history through the report Date Through.
Date of Last HIVQUAL service	Returns the most recent qualifying hivqual service from the client's available history through the report Date Through.
Date Of Last Poverty Level In Span	Returns the most recent qualifying poverty level in span within the configured Date From and Date Through span.
Date of last service	Returns the most recent qualifying service from the client's available history through the report Date Through.
Date of Last Srv Cat In Span	Returns the most recent qualifying service cat in span within the configured Date From and Date Through span.
Date Of Last STI Test In Span	Returns the most recent qualifying sti test in span within the configured Date From and Date Through span.
Date of Last Subservice	Returns the most recent qualifying subservice from the client's available history through the report Date Through.
Date of latest Diagnosis	Returns the date of latest diagnosis from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date of latest diagnosis by ICD9 code	Returns the date of latest diagnosis by icd9 code from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date of latest Diagnosis ICD10	Returns the date of latest diagnosis icd10 from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date of latest ICD9 in a range	Returns the date of latest icd9 in a range from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date of the next PAP smear after abnormal result	Returns the date of the next pap smear after abnormal result from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date prenatal care began	Returns the date prenatal care began from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date transferred in	Returns the date transferred in from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Date transferred out	Returns the date transferred out from the client record or the qualifying related record selected by the field's date and subfilter criteria.

Field Name	Description
Days between appointments	Returns the number of qualifying service or appointment records represented by “Days between appointments”, after applying service-category, subservice, funding, and interval criteria.
Days Enrolled	Returns the client-level “Days Enrolled” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Depress Screen?	Indicates whether the client satisfies the “Depress Screen” condition based on qualifying client or related records.
Diastolic Change	Calculates the difference represented by “Diastolic Change” between the selected earlier and later qualifying values.
Domestic Violence?	Indicates whether the client satisfies the “Domestic Violence” condition based on qualifying client or related records.
Eligible For RSR	Indicates whether the client satisfies the “Eligible For RSR” condition based on qualifying client or related records.
Encrypted UCI	Displays the client’s encrypted unique client identifier.
Encrypted URN	Displays the client’s encrypted unique record number used by the applicable reporting function.
End date of report	Displays the Date Through parameter used to run the custom report.
Enrollment date	Returns the enrollment date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
Enrollment status	Returns the client-level enrollment status, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Enrollment status - RSR	Returns the client-level “Enrollment status - RSR” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Enrollment status (old)	Returns the client-level enrollment status (old), using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Enrollment status across providers	Returns the client-level enrollment status across providers, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Enrollment status by date	Returns the latest applicable enrollment status on or before the configured key date or report Date Through.
Enrollment Status-ADAP	Returns the client-level enrollment status-adap, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Enrollment status-RDR	Returns the client-level “Enrollment status-RDR” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
ER Visits In Period	Returns the number of qualifying service or appointment records represented by “ER Visits In Period” within the configured Date From and Date Through span, after applying service-category, subservice, funding, and interval criteria.
Filipino	Indicates whether Filipino is selected for the client’s Asian subgroup.

Field Name	Description
First ARV Abbreviation	Returns the earliest qualifying arv abbreviation from the client's available history through the report Date Through.
First ARV Haart Classes	Returns the earliest qualifying arv haart classes from the client's available history through the report Date Through.
First ARV Regimen	Returns the earliest qualifying arv regimen from the client's available history through the report Date Through.
First Conception Date	Returns the earliest qualifying conception date from the client's available history through the report Date Through.
First Counseled about HIV risks in Span	Returns the earliest qualifying counseled about hiv risks in span within the configured Date From and Date Through span.
First date of qualitative test	Returns the earliest qualifying date of qualitative test from the client's available history through the report Date Through.
First date specific service received	Returns the earliest qualifying date specific service received from the client's available history through the report Date Through.
First Eligibility Date Field Value	Returns the earliest qualifying eligibility date field value from the client's available history through the report Date Through.
First Eligibility Date Field Value By Funding	Returns the earliest qualifying eligibility date field value by funding from the client's available history through the report Date Through.
First Eligibility Field Value	Returns the earliest qualifying eligibility field value, evaluated through the report Date Through and the field's subfilter criteria.
First Eligibility Field Value By Funding	Returns the earliest qualifying eligibility field value for the selected funding source, evaluated through the report Date Through and the field's subfilter criteria.
First ever service date	Returns the earliest qualifying service date from the client's available history through the report Date Through.
First HH Income In Span	Returns the earliest qualifying hh income in span within the configured Date From and Date Through span.
First HH Size In Span	Returns the earliest qualifying hh size in span within the configured Date From and Date Through span.
First Housing Arr In Span	Returns the earliest qualifying housing arr in span within the configured Date From and Date Through span.
First Ins Codes In Span	Returns the earliest qualifying ins codes in span within the configured Date From and Date Through span.
First Name	Displays the client's first name.
First Poverty Level In Span	Returns the earliest qualifying poverty level in span within the configured Date From and Date Through span.
First Primary Ins Code In Span	Returns the earliest qualifying primary ins code in span within the configured Date From and Date Through span.
First Primary Insurance In Span	Returns the earliest qualifying primary insurance in span within the configured Date From and Date Through span.

Field Name	Description
First Prm. Medical Care In Span	Returns the earliest qualifying primary medical care in span within the configured Date From and Date Through span.
First Qualitative Lab Date	Returns the earliest qualifying qualitative lab date from the client's available history through the report Date Through.
First Qualitative Lab Value	Returns the earliest qualifying qualitative lab value from the client's available history through the report Date Through.
First Quantitative Lab Date	Returns the earliest qualifying quantitative lab date from the client's available history through the report Date Through.
First Quantitative Lab Value	Returns the earliest qualifying quantitative lab value from the client's available history through the report Date Through.
First RSR Housing Arr In Span	Returns the earliest qualifying rsr housing arr in span within the configured Date From and Date Through span.
First Screening Score In Period	Returns the earliest qualifying screening score in period within the configured Date From and Date Through span.
First Secondary Ins Codes In Span	Returns the earliest qualifying secondary ins codes in span within the configured Date From and Date Through span.
First Subform Field Value	Returns the earliest qualifying custom subform field value through the report Date Through, based on the selected form, field, and subfilter criteria.
Fixed user value	Returns the constant value entered in the field-selection configuration for every included report row.
Formatted Field	Returns another selected value after applying the custom report's configured display format.
Full LIS	Returns the client-level "Full LIS" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Functional Status At ART	Returns the client-level functional status at art, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Funding source international version	Returns the client-level funding source international version, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Gap in HIV Medical Visits: EHE	Returns the number of qualifying service or appointment records represented by "Gap in HIV Medical Visits: EHE", after applying service-category, subservice, funding, and interval criteria.
Gender	Displays the client's gender value resolved from the gender reference values.
Gonorrhea Screening	Returns the client-level "Gonorrhea Screening" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Guamanian Or Chamorro	Indicates whether Guamanian or Chamorro is selected for the client's Pacific Islander subgroup.
Haart Classes As of Date	Returns the latest applicable haart classes on or before the configured key date or report Date Through.

Field Name	Description
HAB: Gap in HIV medical visits	Returns the number of qualifying service or appointment records represented by “HAB: Gap in HIV medical visits”, after applying service-category, subservice, funding, and interval criteria.
HAB: HIV medical visit frequency	Returns the client-level “HAB: HIV medical visit frequency” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HAB: HIV viral load suppression	Returns the client-level “HAB: HIV viral load suppression” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HAB: Prescription of antiretroviral therapy	Returns the client-level “HAB: Prescription of antiretroviral therapy” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Had HOPWA Subsidy In Span	Indicates whether the client satisfies the “HOPWA Subsidy In Span” condition based on qualifying client or related records. Within the configured date from and date through span.
Had HOPWA Subsidy Prior Year	Indicates whether the client satisfies the “HOPWA Subsidy Prior Year” condition based on qualifying client or related records. During the prior reporting year.
Had Vaccination	Indicates whether the client satisfies the “Vaccination” condition based on qualifying client or related records.
Has ADAP Funded Drug Services	Indicates whether the client satisfies the “ADAP Funded Drug Services” condition based on qualifying client or related records.
Has Any Drug Service	Indicates whether the client satisfies the “Any Drug Service” condition based on qualifying client or related records.
Has Any Service	Indicates whether the client satisfies the “Any Service” condition based on qualifying client or related records.
Has clinical encounter	Indicates whether the client satisfies the “clinical encounter” condition based on qualifying client or related records.
Has Contract Item	Indicates whether the client satisfies the “Contract Item” condition based on qualifying client or related records.
Has Contract Item By Name	Indicates whether the client satisfies the “Contract Item By Name” condition based on qualifying client or related records.
Has Current ROI	Indicates whether the client satisfies the “Current ROI” condition based on qualifying client or related records.
Has Diagnosis Code	Indicates whether the client satisfies the “diagnosis Code” condition based on qualifying client or related records.
Has Drug Class Change	Indicates whether the client satisfies the “Drug Class Change” condition based on qualifying client or related records.
Has Drug Disbursements In Period	Indicates whether the client satisfies the “Drug Disbursements In Period” condition based on qualifying client or related records. Within the configured date from and date through span.
Has Form	Indicates whether the client satisfies the “Form” condition based on qualifying client or related records.

Field Name	Description
Has HAART Class	Indicates whether the client satisfies the “HAART Class” condition based on qualifying client or related records.
Has HIV Risk Factor	Indicates whether the client satisfies the “HIV Risk Factor” condition based on qualifying client or related records.
Has HOPWA Service In Span	Indicates whether the client satisfies the “HOPWA Service In Span” condition based on qualifying client or related records. Within the configured date from and date through span.
Has Immunization Code	Indicates whether the client satisfies the “Immunization Code” condition based on qualifying client or related records.
Has Immunization In Period	Indicates whether the client satisfies the “Immunization In Period” condition based on qualifying client or related records. Within the configured date from and date through span.
Has Lab Code	Indicates whether the client satisfies the “Lab Code” condition based on qualifying client or related records.
Has Medication	Indicates whether the client satisfies the “Medication” condition based on qualifying client or related records.
Has Medication Code	Indicates whether the client satisfies the “Medication Code” condition based on qualifying client or related records.
Has medication in period	Indicates whether the client satisfies the “medication in period” condition based on qualifying client or related records. Within the configured date from and date through span.
Has Non HOPWA Only Service In Span	Indicates whether the client satisfies the “Non HOPWA Only Service In Span” condition based on qualifying client or related records. Within the configured date from and date through span.
Has OI Prophylaxis	Indicates whether the client satisfies the “OI Prophylaxis” condition based on qualifying client or related records.
Has OI prophylaxis in period	Indicates whether the client satisfies the “OI prophylaxis in period” condition based on qualifying client or related records. Within the configured date from and date through span.
Has OI Treatment	Indicates whether the client satisfies the “OI Treatment” condition based on qualifying client or related records.
Has PCP Proph if indicated	Indicates whether the client satisfies the “PCP Proph if indicated” condition based on qualifying client or related records.
Has Pos HBsAb Since AIDS Diag	Indicates whether the client satisfies the “Pos HBsAb Since AIDS diagnosis” condition based on qualifying client or related records.
Has Preceding Immunizations	Indicates whether the client satisfies the “Preceding Immunizations” condition based on qualifying client or related records.
Has Preceding Services	Indicates whether the client satisfies the “Preceding Services” condition based on qualifying client or related records.
Has primary health care service	Indicates whether the client satisfies the “primary health care service” condition based on qualifying client or related records.
Has Provider	Indicates whether the client satisfies the “Provider” condition based on qualifying client or related records.

Field Name	Description
Has Qualitative Test Result	Indicates whether the client satisfies the “Qualitative Test Result” condition based on qualifying client or related records.
Has Qualitative Test Treatment	Indicates whether the client satisfies the “Qualitative Test Treatment” condition based on qualifying client or related records.
Has Quantitative Lab Value Maintaining Threshold	Indicates whether the client satisfies the “Quantitative Lab Value Maintaining Threshold” condition based on qualifying client or related records.
Has Referral	Indicates whether the client satisfies the “Referral” condition based on qualifying client or related records.
Has Referral Code	Indicates whether the client satisfies the “Referral Code” condition based on qualifying client or related records.
Has referral of specific type	Indicates whether the client satisfies the “referral of specific type” condition based on qualifying client or related records.
Has referral type with status	Indicates whether the client satisfies the “referral type with status” condition based on qualifying client or related records.
Has RSR Defined Funded Service	Indicates whether the client satisfies the “RSR Defined Funded Service” condition based on qualifying client or related records.
Has RSR Service For Funded Provider	Indicates whether the client satisfies the “RSR Service For Funded Provider” condition based on qualifying client or related records.
Has RW Funded Service	Indicates whether the client satisfies the “Ryan White funded Service” condition based on qualifying client or related records.
Has RW Funded Service In Span	Indicates whether the client satisfies the “Ryan White funded Service In Span” condition based on qualifying client or related records. Within the configured date from and date through span.
Has RWHAP or EHE Service	Indicates whether the client satisfies the “RWHAP or EHE Service” condition based on qualifying client or related records.
Has Screening Code	Indicates whether the client satisfies the “Screening Code” condition based on qualifying client or related records.
Has Screening Lab Code	Indicates whether the client satisfies the “Screening Lab Code” condition based on qualifying client or related records.
Has Sec. 3 HOPWA Srv In Span	Indicates whether the client satisfies the “Sec. 3 HOPWA service In Span” condition based on qualifying client or related records. Within the configured date from and date through span.
Has Service Code	Indicates whether the client satisfies the “Service Code” condition based on qualifying client or related records.
Has Specific STI Test In Period	Indicates whether the client satisfies the “Specific STI Test In Period” condition based on qualifying client or related records. Within the configured date from and date through span.
Has STI Test In Period	Indicates whether the client satisfies the “STI Test In Period” condition based on qualifying client or related records. Within the configured date from and date through span.
Has Subform Field	Indicates whether the client satisfies the “Subform Field” condition based on qualifying client or related records.

Field Name	Description
Has Subsequent Immunizations	Indicates whether the client satisfies the “Subsequent Immunizations” condition based on qualifying client or related records.
Has Subsequent Services	Indicates whether the client satisfies the “Subsequent Services” condition based on qualifying client or related records.
Height At ART	Returns the client-level height at art selected or calculated from qualifying vital-sign, lab, or screening records.
Height At ART (cm)	Returns the client-level height at art (cm) selected or calculated from qualifying vital-sign, lab, or screening records.
Hemophiliac HIV risk factor	Indicates whether hemophilia-related blood exposure is selected as an HIV risk factor for the client.
Hepatitis B Screening	Returns the client-level “Hepatitis B Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Hepatitis B Vaccination	Returns the client-level “Hepatitis B Vaccination” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Heterosexual HIV risk factor	Indicates whether heterosexual contact is selected as an HIV risk factor for the client.
High BMI	Returns the client-level high bmi selected or calculated from qualifying vital-sign, lab, or screening records.
High Diastolic	Returns the client-level high diastolic selected or calculated from qualifying vital-sign, lab, or screening records.
High Height	Returns the client-level high height selected or calculated from qualifying vital-sign, lab, or screening records.
High Pulse	Returns the client-level high pulse selected or calculated from qualifying vital-sign, lab, or screening records.
High Risk Insurance	Returns the client-level high risk insurance, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
High Risk Pool?	Indicates whether the client satisfies the “High Risk Pool” condition based on qualifying client or related records.
High Systolic	Returns the client-level high systolic selected or calculated from qualifying vital-sign, lab, or screening records.
High Temperature	Returns the client-level high temperature selected or calculated from qualifying vital-sign, lab, or screening records.
High Weight	Returns the client-level high weight selected or calculated from qualifying vital-sign, lab, or screening records.
Highest Quantitative Lab Date	Returns the highest qualifying quantitative lab date through the report Date Through, using the field’s test and subfilter criteria.
Highest Quantitative Lab Value	Returns the highest qualifying quantitative lab value through the report Date Through, using the field’s test and subfilter criteria.
Highest Screening Score In Period	Returns the highest qualifying screening score in period within the configured Date From and Date Through span, using the field’s test and subfilter criteria.

Field Name	Description
HIP 1st Service	Returns the client-level hip 1st service, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
HIP Date Closed	Returns the hip date closed from the client record or the qualifying related record selected by the field's date and subfilter criteria.
HIP Enrl Date	Returns the hip enrollment date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
HIP Enrl Status	Returns the client-level hip enrollment status, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
HIP Last Service	Returns the client-level hip last service, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Hispanic	Indicates whether the client is recorded as Hispanic, Latino/a, or Spanish origin.
Hispanic ethnicity	Displays the client's Hispanic ethnicity value using the configured Yes/No/Unknown reference values.
HIV Date Estimated	Indicates whether the HIV diagnosis date on the client record is marked as estimated.
HIV Link Date	Returns the hiv link date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
HIV Pos Test Date	Returns the hiv pos test date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
HIV Positive	Returns the client-level "HIV Positive" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
HIV Posttest counsld (RDR)	Returns the client-level "HIV Posttest counsld (RDR)" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HIV pretest counseling (RDR)	Returns the client-level "HIV pretest counseling (RDR)" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HIV Risk Factor	Displays the client's HIV risk-factor category derived from the selected risk-factor flags.
HIV Status	Displays the HIV status recorded for the client.
HIV Status By Date	Returns the latest applicable hiv status on or before the configured key date or report Date Through.
HIV Status of Newborn	Returns the client-level hiv status of newborn, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
HIV tested (RDR)	Returns the client-level "HIV tested (RDR)" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HIVQUAL Export?	Indicates whether the client satisfies the "HIVQUAL Export" condition based on qualifying client or related records.

Field Name	Description
HOPWA Age Category	Returns the client-level “HOPWA Age Category” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA Chronic Homelessness	Returns the client-level “HOPWA Chronic Homelessness” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA Enroll Date	Returns the hopwa enroll date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
HOPWA Exit Date	Returns the hopwa exit date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
HOPWA NonSTRMU Housing By Sbs	Returns the client-level “HOPWA NonSTRMU Housing By subservice” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA Pre-Enrollment Housing Situation	Returns the client-level “HOPWA Pre-Enrollment Housing Situation” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA STRMU Exit Outcome	Returns the client-level “HOPWA STRMU Exit Outcome” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA STRMU Housing By Sbs	Returns the client-level “HOPWA STRMU Housing By subservice” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA TBRA Exit Outcome	Returns the client-level “HOPWA TBRA Exit Outcome” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA Trans Facility Outcome	Returns the client-level “HOPWA Trans Facility Outcome” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
HOPWA Veteran Status	Returns the client-level “HOPWA Veteran Status” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Hospital Admissions In Period	Returns the client-level “hospitalital Admissions In Period” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Household Income	Returns the client-level “Household Income” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Household Size	Returns the client-level “Household Size” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Housing Arr - RSR CLD	Returns the client-level “Housing Arr - RSR CLD” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Housing status	Returns the client-level housing status, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.

Field Name	Description
Housing status (RSR)	Returns the client-level “Housing status (RSR)” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Housing Status Date	Returns the housing status date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
HRSA visits by Service Category (RDR)	Returns the number of qualifying service or appointment records represented by “HRSA visits by Service Category (RDR)”, after applying service-category, subservice, funding, and interval criteria.
IDU	Indicates whether injection drug use is selected as an HIV risk factor for the client.
IGRA Result	Returns the client-level igra result, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Imm Or Proc Count After Imm Or Proc	Returns the number of qualifying records or items represented by “Imm Or Proc Count After Imm Or Proc”. The count is record-based unless the field explicitly defines unduplicated clients.
Imm Or Proc Count Before Imm Or Proc	Returns the number of qualifying records or items represented by “Imm Or Proc Count Before Imm Or Proc”. The count is record-based unless the field explicitly defines unduplicated clients.
Immunization And Procedure Count	Returns the number of qualifying records or items represented by “Immunization And Procedure Count”. The count is record-based unless the field explicitly defines unduplicated clients.
Immunization Count	Returns the number of qualifying records or items represented by “Immunization Count”. The count is record-based unless the field explicitly defines unduplicated clients.
Indian Health Service	Indicates whether Indian Health Service coverage is selected in the applicable insurance assessment.
Influenza vaccination	Returns the client-level “Influenza vaccination” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
International version	Indicates whether the result or configuration applies to CAREWare’s international-version data elements.
Is ART funded by US Govt: International version	Indicates whether the client satisfies the “ART funded by US Govt: International version” condition based on qualifying client or related records.
Is client race Asian?	Indicates whether the client has any Asian race or Asian subgroup selection.
Is date of birth estimated?	Indicates whether the client’s date of birth is marked as estimated.
Is Part D Client	Indicates whether the client satisfies the “Part D Client” condition based on qualifying client or related records.
Is RW Eligible In Span	Indicates whether the client satisfies the “RW Eligible In Span” condition based on qualifying client or related records. Within the configured date from and date through span.
Japanese	Indicates whether Japanese is selected for the client’s Asian subgroup.
Korean	Indicates whether Korean is selected for the client’s Asian subgroup.

Field Name	Description
Lab interval count	Returns the number of qualifying records or items represented by “Lab interval count”. The count is record-based unless the field explicitly defines unduplicated clients.
Last Billing Insurer	Returns the most recent qualifying billing insurer from the client’s available history through the report Date Through.
Last Billing Notes	Returns the most recent qualifying billing notes from the client’s available history through the report Date Through.
Last Billing PrimaryID	Returns the most recent qualifying billing primaryid from the client’s available history through the report Date Through.
Last Billing SecondaryID	Returns the most recent qualifying billing secondaryid from the client’s available history through the report Date Through.
Last Blood Pressure	Returns the most recent qualifying blood pressure from the client’s available history through the report Date Through.
Last BMI	Returns the most recent qualifying bmi from the client’s available history through the report Date Through.
Last Case Note	Returns the most recent qualifying case note from the client’s available history through the report Date Through.
Last Case Note Date	Returns the most recent qualifying case note date from the client’s available history through the report Date Through.
Last Counseled about HIV risks in Span	Returns the most recent qualifying counseled about hiv risks in span within the configured Date From and Date Through span.
Last Date PCP Preventive Med Started	Returns the most recent qualifying date pcp preventive medication started from the client’s available history through the report Date Through.
Last Diastolic	Returns the most recent qualifying diastolic from the client’s available history through the report Date Through.
Last Eligibility Field Value	Returns the most recent qualifying eligibility field value, evaluated through the report Date Through and the field’s subfilter criteria.
Last Eligibility Field Value By Funding	Returns the most recent qualifying eligibility field value for the selected funding source, evaluated through the report Date Through and the field’s subfilter criteria.
Last Height	Returns the most recent qualifying height from the client’s available history through the report Date Through.
Last HH Income In Span	Returns the most recent qualifying hh income in span within the configured Date From and Date Through span.
Last HH Size In Span	Returns the most recent qualifying hh size in span within the configured Date From and Date Through span.
Last HOPWA Subsidy Date	Returns the most recent qualifying hopwa subsidy date from the client’s available history through the report Date Through.
Last Housing Arr In Span	Returns the most recent qualifying housing arr in span within the configured Date From and Date Through span.
Last ICD10 Diagnosis Date	Returns the most recent qualifying icd10 diagnosis date from the client’s available history through the report Date Through.

Field Name	Description
Last Ins Codes In Span	Returns the most recent qualifying ins codes in span within the configured Date From and Date Through span.
Last Name	Displays the client's last name.
Last OI Prophylaxis Medication	Returns the most recent qualifying oi prophylaxis medication from the client's available history through the report Date Through.
Last Poverty Level In Span	Returns the most recent qualifying poverty level in span within the configured Date From and Date Through span.
Last Preg Outcome In Span	Returns the most recent qualifying pregnancy outcome in span within the configured Date From and Date Through span.
Last Primary Ins Code In Span	Returns the most recent qualifying primary ins code in span within the configured Date From and Date Through span.
Last Primary Insurance In Span	Returns the most recent qualifying primary insurance in span within the configured Date From and Date Through span.
Last Prm. Medical Care In Span	Returns the most recent qualifying primary medical care in span within the configured Date From and Date Through span.
Last Pulse	Returns the most recent qualifying pulse from the client's available history through the report Date Through.
Last Qualitative Action	Returns the most recent qualifying qualitative action from the client's available history through the report Date Through.
Last Qualitative Date With Values	Returns the most recent qualifying qualitative date with values from the client's available history through the report Date Through.
Last Qualitative Lab Date	Returns the most recent qualifying qualitative lab date from the client's available history through the report Date Through.
Last Qualitative Lab Value	Returns the most recent qualifying qualitative lab value from the client's available history through the report Date Through.
Last Qualitative Result With Values	Returns the most recent qualifying qualitative result with values from the client's available history through the report Date Through.
Last Qualitative Treatment	Returns the most recent qualifying qualitative treatment from the client's available history through the report Date Through.
Last Quantitative Date With Values	Returns the most recent qualifying quantitative date with values from the client's available history through the report Date Through.
Last Quantitative Lab Date	Returns the most recent qualifying quantitative lab date from the client's available history through the report Date Through.
Last Quantitative Lab Operator	Returns the most recent qualifying quantitative lab operator from the client's available history through the report Date Through.
Last Quantitative Lab Value	Returns the most recent qualifying quantitative lab value from the client's available history through the report Date Through.
Last Quantitative Result With Values	Returns the most recent qualifying quantitative result with values from the client's available history through the report Date Through.
Last ROI End Date	Returns the most recent qualifying roi end date from the client's available history through the report Date Through.

Field Name	Description
Last ROI Start Date	Returns the most recent qualifying roi start date from the client's available history through the report Date Through.
Last RSR Housing Arr In Span	Returns the most recent qualifying rsr housing arr in span within the configured Date From and Date Through span.
Last Screening OID	Returns the most recent qualifying screening oid from the client's available history through the report Date Through.
Last Screening Score In Period	Returns the most recent qualifying screening score in period within the configured Date From and Date Through span.
Last Secondary Ins Codes In Span	Returns the most recent qualifying secondary ins codes in span within the configured Date From and Date Through span.
Last Service Field Val In Category	Returns the most recent qualifying custom service field value in the selected service category, evaluated through the report Date Through.
Last Service Field Val In Contract	Returns the most recent qualifying custom service field value under the selected contract, evaluated through the report Date Through.
Last Service Field Value	Returns the most recent qualifying custom service field value, evaluated through the report Date Through.
Last Service In Category	Returns the most recent qualifying service in category from the client's available history through the report Date Through.
Last Service In Contract	Returns the most recent qualifying service in contract from the client's available history through the report Date Through.
Last stop date of any TB prophylaxis medication	Returns the most recent qualifying stop date of any tb prophylaxis medication from the client's available history through the report Date Through.
Last stop date of any TB treatment medication	Returns the most recent qualifying stop date of any tb treatment medication from the client's available history through the report Date Through.
Last Subform Date Field Value	Returns the most recent qualifying subform date field value from the client's available history through the report Date Through.
Last Subform Field Value	Returns the most recent qualifying custom subform field value through the report Date Through, based on the selected form, field, and subfilter criteria.
Last Systolic	Returns the most recent qualifying systolic from the client's available history through the report Date Through.
Last Temperature	Returns the most recent qualifying temperature from the client's available history through the report Date Through.
Last vaccination date	Returns the most recent qualifying vaccination date from the client's available history through the report Date Through.
Last Vital Sign Date	Returns the most recent qualifying vital sign date from the client's available history through the report Date Through.
Last Weight	Returns the most recent qualifying weight from the client's available history through the report Date Through.
Latest estimated conception date	Returns the most recent qualifying estimated conception date from the client's available history through the report Date Through.
Legacy eUCI	Displays the legacy encrypted unique client identifier stored for the client.

Field Name	Description
Legacy URN	Displays the legacy unique record number stored for the client.
Lipid Screening	Returns the client-level “Lipid Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Low BMI	Returns the client-level low bmi selected or calculated from qualifying vital-sign, lab, or screening records.
Low Diastolic	Returns the client-level low diastolic selected or calculated from qualifying vital-sign, lab, or screening records.
Low Height	Returns the client-level low height selected or calculated from qualifying vital-sign, lab, or screening records.
Low Pulse	Returns the client-level low pulse selected or calculated from qualifying vital-sign, lab, or screening records.
Low Quantitative Lab Date	Returns the lowest qualifying quantitative lab date through the report Date Through, using the field’s test and subfilter criteria.
Low Systolic	Returns the client-level low systolic selected or calculated from qualifying vital-sign, lab, or screening records.
Low Temperature	Returns the client-level low temperature selected or calculated from qualifying vital-sign, lab, or screening records.
Low Weight	Returns the client-level low weight selected or calculated from qualifying vital-sign, lab, or screening records.
Lowest Adherence Rate	Returns the lowest qualifying adherence rate through the report Date Through, using the field’s test and subfilter criteria.
Lowest Quantitative Lab Value	Returns the lowest qualifying quantitative lab value through the report Date Through, using the field’s test and subfilter criteria.
Lowest Screening Score In Period	Returns the lowest qualifying screening score in period within the configured Date From and Date Through span, using the field’s test and subfilter criteria.
MAC prophylaxis	Returns the client-level “MAC prophylaxis” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Mail	Indicates whether mail is an approved or selected communication method for the client.
Mailing Address	Displays the client’s mailing street address.
Mailing City	Displays the city from the client’s mailing address.
Mailing State	Displays the state from the client’s mailing address.
Mailing ZIP	Displays the ZIP code from the client’s mailing address.
Male to Male sexual contact (MSM)	Indicates whether male-to-male sexual contact is selected as an HIV risk factor for the client.
Marital Status	Displays the client’s marital-status value.
Max ARV Count In Span	Returns the number of qualifying records or items represented by “Max ARV Count In Span” within the configured Date From and Date Through span. The count is record-based unless the field explicitly defines unduplicated clients.

Field Name	Description
Medicaid, CHIP or Other Public Plan	Returns the client-level “Medicaid, CHIP or Other Public Plan” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Medicare (unspecified)	Returns the client-level “Medicare (unspecified)” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Medicare Insurance	Returns the client-level medicare insurance, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Medicare Part A/B	Returns the client-level “Medicare Part A/B” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Medicare Part C	Returns the client-level “Medicare Part C” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Medicare Part D	Returns the client-level “Medicare Part D” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Medication has ICD10	Returns the client-level medication has icd10, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Medication has Indication	Returns the client-level medication has indication, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Medication Start Date	Returns the medication start date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
Medications By ICD10	Returns the client-level medications by icd10, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Medications by indication	Returns the client-level medications by indication, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Memo	Returns the client-level “Memo” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Mental Health Screening	Returns the client-level “Mental Health Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Mexican, Mexican American, Chicano/a	Indicates whether Mexican, Mexican American, or Chicano/a is selected for the client’s Hispanic subgroup.
Middle Name	Displays the client’s middle name.
MSM And IDU	Indicates whether both male-to-male sexual contact and injection drug use are selected as HIV risk factors.
Name	Displays the client name using the report field’s configured name format.
NASTAD - Dually Eligible in Span	Returns the client-level “NASTAD - Dually Eligible in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.

Field Name	Description
NASTAD – Indian Health Services in Span	Returns the client-level “NASTAD – Indian Health Services in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD – Insurance Unknown in Span	Returns the client-level “NASTAD – Insurance Unknown in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD – Medicaid Only in Span	Returns the client-level “NASTAD – Medicaid Only in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD - Medicare Only in Span	Returns the client-level “NASTAD - Medicare Only in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD – No Insurance in Span	Returns the client-level “NASTAD – No Insurance in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD – Other Insurance in Span	Returns the client-level “NASTAD – Other Insurance in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD – Private Insurance in Span	Returns the client-level “NASTAD – Private Insurance in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
NASTAD – VA / Military in Span	Returns the client-level “NASTAD – VA / Military in Span” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Native Hawaiian	Indicates whether Native Hawaiian is selected for the client’s Pacific Islander subgroup.
Need Men. Heal. Ref.?	Indicates whether the client satisfies the “Need Men. Heal. referral” condition based on qualifying client or related records.
Newly enrolled clients	Returns the client-level “Newly enrolled clients” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
No Insurance	Indicates whether the applicable insurance assessment records no insurance coverage.
Non antiretroviral medications	Returns the client-level non antiretroviral medications, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Num appts by Subservice	Returns the number of qualifying service or appointment records represented by “number appts by Subservice”, after applying service-category, subservice, funding, and interval criteria.
Number ARV active ingredients	Returns the client-level “Number ARV active ingredients” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Number newborns with HIV status	Returns the client-level number newborns with hiv status, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.

Field Name	Description
Number of appts	Returns the number of qualifying records or items represented by “Number of appts”. The count is record-based unless the field explicitly defines unduplicated clients.
Number of ARV active ingredients	Returns the number of qualifying records or items represented by “Number of ARV active ingredients”. The count is record-based unless the field explicitly defines unduplicated clients.
Number of ARV active ingredients on a specific date	Returns the number of qualifying records or items represented by “Number of ARV active ingredients on a specific date”. The count is record-based unless the field explicitly defines unduplicated clients.
Number of days active	Returns the number of qualifying records or items represented by “Number of days active”. The count is record-based unless the field explicitly defines unduplicated clients.
Number of missed appointments by subservice	Returns the number of qualifying records or items represented by “Number of missed appointments by subservice”. The count is record-based unless the field explicitly defines unduplicated clients.
Number of missed appointments in Span	Returns the number of qualifying records or items represented by “Number of missed appointments in Span” within the configured Date From and Date Through span. The count is record-based unless the field explicitly defines unduplicated clients.
Number of pregnancy outcomes	Returns the number of qualifying records or items represented by “Number of pregnancy outcomes”. The count is record-based unless the field explicitly defines unduplicated clients.
Oral Exam	Returns the client-level “Oral Exam” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Other Asian	Indicates whether Other Asian is selected for the client’s Asian subgroup.
Other HIV risk	Indicates whether an HIV risk factor outside the standard listed categories is selected for the client.
Other HIV risk described	Displays the text describing the client’s other HIV risk factor.
Other Insurance Description	Returns the client-level other insurance description, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Other Pacific Islander	Indicates whether Other Pacific Islander is selected for the client’s Pacific Islander subgroup.
Other Plan	Returns the client-level “Other Plan” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Other public (e.g. Champus, VA)	Returns the client-level “Other public (e.g. Champus, VA)” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Other race	Indicates whether Other Race is selected for the client.
Pacific Islander race	Indicates whether Native Hawaiian or Other Pacific Islander is selected for the client’s race.

Field Name	Description
Parners notified (RDR)	Returns the client-level “Parners notified (RDR)” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Percent Change in body mass index	Calculates the percentage or rate represented by “Percent Change in body mass index” from the qualifying numerator and denominator values defined by the field and its date criteria.
Percentage of pregnant women prescribed ART	Calculates the percentage or rate represented by “Percentage of pregnant women prescribed ART” from the qualifying numerator and denominator values defined by the field and its date criteria.
Percentage with >=2 CD4 Counts	Returns the number of qualifying records or items represented by “Percentage with >=2 CD4 Counts”. The count is record-based unless the field explicitly defines unduplicated clients.
Perinatal HIV transmission risk	Returns the client-level perinatal hiv transmission risk, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Phone	Displays the client’s primary phone number.
Phone Type	Displays the type assigned to the client’s primary phone number.
Physician name	Displays the physician linked to the client record.
Pneumococcal Vaccination	Returns the client-level “Pneumococcal Vaccination” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Poverty level	Returns the client-level “Poverty level” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
PPD Result for Period	Returns the client-level ppd result for period, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Pre-ART reason	Returns the client-level pre-art reason, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Preferred Language	Displays the client’s preferred language.
Preferred Name	Displays the client’s preferred name.
Pregnant In Period	Returns the client-level “pregnancynant In Period” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Prescribed HAART	Indicates whether the client satisfies the “Prescribed HAART” condition based on qualifying client or related records.
Prescribed HAART (RSR)	Indicates whether the client satisfies the “Prescribed HAART (RSR)” condition based on qualifying client or related records.
Previous Qualitative Lab Date	Returns the qualifying qualitative lab date immediately preceding the current or latest selected record.
Previous Qualitative Lab Value	Returns the qualifying qualitative lab value immediately preceding the current or latest selected record.

Field Name	Description
Previous Quantitative Lab Date	Returns the qualifying quantitative lab date immediately preceding the current or latest selected record.
Previous Quantitative Lab Value	Returns the qualifying quantitative lab value immediately preceding the current or latest selected record.
Previous Regimen	Returns the qualifying regimen immediately preceding the current or latest selected record.
Previous Regimen Line	Returns the qualifying regimen line immediately preceding the current or latest selected record.
Previous Regimen Start Date	Returns the qualifying regimen start date immediately preceding the current or latest selected record.
Previous Regimen Stop Date	Returns the qualifying regimen stop date immediately preceding the current or latest selected record.
Previous Subform Field Value	Returns the custom subform field value immediately preceding the selected or latest qualifying subform record.
Primary health insurance type	Returns the client-level primary health insurance type, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Primary key	Displays the client record's internal unique identifier; use it for technical reconciliation or joins rather than as a client-facing identifier.
Primary Provider	Returns the client-level primary provider, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Prior ARV Treatment	Returns the client-level "Prior ARV Treatment" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Private - Employer	Returns the client-level "Private - Employer" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Private - Individual	Returns the client-level "Private - Individual" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Private (Deprecated)	Returns the client-level "Private (Deprecated)" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Provider domains clinical data shared by	Returns the client-level provider domains clinical data shared by, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Provider domains clinical data shared with	Returns the client-level provider domains clinical data shared with, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Provider domains service data shared by	Returns the client-level provider domains service data shared by, using the client record or the most applicable related record selected by the field's date and subfilter criteria.

Field Name	Description
Provider domains service date shared with	Returns the provider domains service date shared with from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Provider memo	Displays the provider-specific memo associated with the client.
Psychiatric History?	Indicates whether the client satisfies the "Psychiatric History" condition based on qualifying client or related records.
Psychosocial Assessment?	Indicates whether the client satisfies the "Psychosocial Assessment" condition based on qualifying client or related records.
PTSD?	Indicates whether the client satisfies the "PTSD" condition based on qualifying client or related records.
Puerto Rican	Indicates whether Puerto Rican is selected for the client's Hispanic subgroup.
Q1 Mental Health	Returns the client-level "Q1 Mental Health" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q1 Mnt Hlth Trt	Returns the client-level "Q1 mental health Trt" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q1 Sbst Abuse Trt	Returns the client-level "Q1 substance Abuse Trt" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q1 Subst Abuse	Returns the client-level "Q1 Subst Abuse" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q2 Mental Health	Returns the client-level "Q2 Mental Health" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q2 Mnt Hlth Trt	Returns the client-level "Q2 mental health Trt" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q2 Sbst Abuse Trt	Returns the client-level "Q2 substance Abuse Trt" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q2 Subst Abuse	Returns the client-level "Q2 Subst Abuse" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q3 Mental Health	Returns the client-level "Q3 Mental Health" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q3 Mnt Hlth Trt	Returns the client-level "Q3 mental health Trt" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Q3 Sbst Abuse Trt	Returns the client-level "Q3 substance Abuse Trt" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.

Field Name	Description
Q3 Subst Abuse	Returns the client-level “Q3 Subst Abuse” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Q4 Mental Health	Returns the client-level “Q4 Mental Health” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Q4 Mnt Hlth Trt	Returns the client-level “Q4 mental health Trt” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Q4 Sbst Abuse Trt	Returns the client-level “Q4 substance Abuse Trt” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Q4 Subst Abuse	Returns the client-level “Q4 Subst Abuse” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Qualitative Result Last Date	Returns the qualitative result last date from the client record or the qualifying related record selected by the field’s date and subfilter criteria.
Quantitative BMI Change	Calculates the difference represented by “Quantitative BMI Change” between the selected earlier and later qualifying values.
Quantitative Lab Amount Change	Calculates the difference represented by “Quantitative Lab Amount Change” between the selected earlier and later qualifying values.
Quantitative Lab Log Change	Calculates the logarithmic change between the selected earlier and later qualifying quantitative lab values.
Quantitative Lab Percent Change	Calculates the percentage or rate represented by “Quantitative Lab Percent Change” from the qualifying numerator and denominator values defined by the field and its date criteria.
Quantitative Lab Value below Threshold for Number of Days	Returns the client-level quantitative lab value below threshold for number of days selected or calculated from qualifying vital-sign, lab, or screening records.
Quantitative Weight Change	Calculates the difference represented by “Quantitative Weight Change” between the selected earlier and later qualifying values.
Race	Displays the client’s race selections using the report’s configured race display logic.
Race for RDR	Returns the client-level “Race for RDR” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Race/Ethnicity	Returns the combined race and ethnicity category used by the selected reporting definition.
Rcvd Adherence Service	Indicates whether the client satisfies the “Adherence Service” condition based on qualifying client or related records.
Rcvd APA Service	Indicates whether the client satisfies the “APA Service” condition based on qualifying client or related records.
Rcvd Case Mgt (NM) Service	Indicates whether the client satisfies the “Case Mgt (NM) Service” condition based on qualifying client or related records.

Field Name	Description
Rcvd Child Care Service	Indicates whether the client satisfies the “Child Care Service” condition based on qualifying client or related records.
Rcvd Development Assess Service	Indicates whether the client satisfies the “Development Assess Service” condition based on qualifying client or related records.
Rcvd Fin. Ass. Service	Indicates whether the client satisfies the “Fin. Ass. Service” condition based on qualifying client or related records.
Rcvd Food Bank Service	Indicates whether the client satisfies the “Food Bank Service” condition based on qualifying client or related records.
Rcvd Health Care Referral Service	Indicates whether the client satisfies the “Health Care Referral Service” condition based on qualifying client or related records.
Rcvd Health/Risk Ed Service	Indicates whether the client satisfies the “Health/Risk Ed Service” condition based on qualifying client or related records.
Rcvd HIP Service	Indicates whether the client satisfies the “HIP Service” condition based on qualifying client or related records.
Rcvd Housing Service	Indicates whether the client satisfies the “Housing Service” condition based on qualifying client or related records.
Rcvd Legal Service	Indicates whether the client satisfies the “Legal Service” condition based on qualifying client or related records.
Rcvd Linguistic Service	Indicates whether the client satisfies the “Linguistic Service” condition based on qualifying client or related records.
Rcvd Outreach Service	Indicates whether the client satisfies the “Outreach Service” condition based on qualifying client or related records.
Rcvd Perm Planning Service	Indicates whether the client satisfies the “Perm Planning Service” condition based on qualifying client or related records.
Rcvd Psycho Social Service	Indicates whether the client satisfies the “Psycho Social Service” condition based on qualifying client or related records.
Rcvd Rehabilitation Service	Indicates whether the client satisfies the “Rehabilitation Service” condition based on qualifying client or related records.
Rcvd Res. Subst Abuse Service	Indicates whether the client satisfies the “Res. Subst Abuse Service” condition based on qualifying client or related records.
Rcvd Respite Care Service	Indicates whether the client satisfies the “Respite Care Service” condition based on qualifying client or related records.
Rcvd Transportation Service	Indicates whether the client satisfies the “Transportation Service” condition based on qualifying client or related records.
Reason ART Discontinued	Returns the client-level reason art discontinued, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Received ADAP Funded Insurance	Indicates whether the client satisfies the “ADAP Funded Insurance” condition based on qualifying client or related records.
Received copay/deductible assistance	Indicates whether the client satisfies the “copay/deductible assistance” condition based on qualifying client or related records.

Field Name	Description
Received Diagnosis ICD9	Indicates whether the client satisfies the “diagnosis ICD9” condition based on qualifying client or related records.
Received FULL insurance premium assistance	Indicates whether the client satisfies the “FULL insurance premium assistance” condition based on qualifying client or related records.
Received High Risk ADAP Services	Indicates whether the client satisfies the “High Risk ADAP Services” condition based on qualifying client or related records.
Received HIVQUAL referral	Indicates whether the client satisfies the “HIVQUAL referral” condition based on qualifying client or related records.
Received HIVQUAL subservice	Indicates whether the client satisfies the “HIVQUAL subservice” condition based on qualifying client or related records.
Received ICD10 Diagnosis	Indicates whether the client satisfies the “ICD10 diagnosis” condition based on qualifying client or related records.
Received Lab or Screening	Indicates whether the client satisfies the “Lab or Screening” condition based on qualifying client or related records.
Received PARTIAL insurance premium assistance	Indicates whether the client satisfies the “PARTIAL insurance premium assistance” condition based on qualifying client or related records.
Received screening action	Indicates whether the client satisfies the “screening action” condition based on qualifying client or related records.
Received service- RDR	Indicates whether the client satisfies the “service- RDR” condition based on qualifying client or related records.
Received STI Action	Indicates whether the client satisfies the “STI Action” condition based on qualifying client or related records.
Received STI Test	Indicates whether the client satisfies the “STI Test” condition based on qualifying client or related records.
Received subservice	Indicates whether the client satisfies the “subservice” condition based on qualifying client or related records.
Received Test	Indicates whether the client satisfies the “Test” condition based on qualifying client or related records.
Received Test Since HIV Diagnosis	Indicates whether the client satisfies the “Test Since HIV diagnosis” condition based on qualifying client or related records.
Received test-RDR	Indicates whether the client satisfies the “test-RDR” condition based on qualifying client or related records.
Referral for experimental services (Part C)	Returns the client-level referral for experimental services (part c), using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Referral for outside services (Part C)	Returns the client-level referral for outside services (part c), using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Referrals By Category	Returns the client-level referrals by category, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Referred for Serv. Category	Returns the client-level referred for serv. category, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.

Field Name	Description
Regimen Line In Span	Returns the client-level regimen line in span, using the client record or the most applicable related record selected by the field's date and subfilter criteria. Within the configured date from and date through span.
Resulted HIVQUAL referral	Returns the client-level "Resulted HIVQUAL referral" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
RSR Has PCP Prophylaxis	Returns the client-level "RSR Has PCP Prophylaxis" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
RSR Housing Arr	Returns the client-level "RSR Housing Arr" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
RSR Prescribed ART	Returns the client-level "RSR Prescribed ART" result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
RSR Visits At RW Funded Provider	Returns the number of qualifying service or appointment records represented by "RSR Visits At Ryan White funded Provider", after applying service-category, subservice, funding, and interval criteria.
RSR ZIP	Displays the ZIP code value formatted or derived for Ryan White Services Report reporting.
RW Eligibility Status By Date	Returns the latest applicable rw eligibility status on or before the configured key date or report Date Through.
RW-funded visits in span	Returns the number of qualifying service or appointment records represented by "Ryan White-funded visits in span" within the configured Date From and Date Through span, after applying service-category, subservice, funding, and interval criteria.
Samoan	Indicates whether Samoan is selected for the client's Pacific Islander subgroup.
Screened For Hep B	Indicates whether the client satisfies the "Screened For Hep B" condition based on qualifying client or related records.
Screened For Hep C	Indicates whether the client satisfies the "Screened For Hep C" condition based on qualifying client or related records.
Screened For HepB Since HIV DX	Indicates whether the client satisfies the "Screened For HepB Since HIV DX" condition based on qualifying client or related records.
Screened For HepC Since HIV DX	Indicates whether the client satisfies the "Screened For HepC Since HIV DX" condition based on qualifying client or related records.
Screened For TB	Indicates whether the client satisfies the "Screened For TB" condition based on qualifying client or related records.
Screened For TB Since HIV DX	Indicates whether the client satisfies the "Screened For TB Since HIV DX" condition based on qualifying client or related records.
Service category interval count	Returns the number of qualifying records or items represented by "Service category interval count". The count is record-based unless the field explicitly defines unduplicated clients.

Field Name	Description
Service Category Total	Returns the aggregate total represented by “Service Category Total”, using qualifying related records and the field’s subfilter criteria.
Services Shared By Client	Returns the client-level services shared by client, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Sex At Birth	Displays the client’s sex-at-birth value.
Sleep. Hab. Assess?	Indicates whether the client satisfies the “Sleep. Hab. Assess” condition based on qualifying client or related records.
Source primary medical care	Returns the client-level “Source primary medical care” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
State	Displays the state linked to the client’s address.
State NO	Displays the state number or code associated with the client’s address.
Subs. Use Alcohol?	Indicates whether the client satisfies the “Subs. Use Alcohol” condition based on qualifying client or related records.
Subs. Use Cocaine Inj?	Indicates whether the client satisfies the “Subs. Use Cocaine Inj” condition based on qualifying client or related records.
Subs. Use Cocaine?	Indicates whether the client satisfies the “Subs. Use Cocaine” condition based on qualifying client or related records.
Subs. Use Cur. In Treat.?	Indicates whether the client satisfies the “Subs. Use Cur. In Treat.” condition based on qualifying client or related records.
Subs. Use Current?	Indicates whether the client satisfies the “Subs. Use Current” condition based on qualifying client or related records.
Subs. Use Heroin Inj.?	Indicates whether the client satisfies the “Subs. Use Heroin Inj.” condition based on qualifying client or related records.
Subs. Use Heroin?	Indicates whether the client satisfies the “Subs. Use Heroin” condition based on qualifying client or related records.
Subs. Use Hist. 2 Yrs?	Indicates whether the client satisfies the “Subs. Use Hist. 2 Yrs” condition based on qualifying client or related records.
Subs. Use Identified?	Indicates whether the client satisfies the “Subs. Use Identified” condition based on qualifying client or related records.
Subs. Use Marijuana?	Indicates whether the client satisfies the “Subs. Use Marijuana” condition based on qualifying client or related records.
Subs. Use Other Subs?	Indicates whether the client satisfies the “Subs. Use Other Subs” condition based on qualifying client or related records.
Subs. Use Pills?	Indicates whether the client satisfies the “Subs. Use Pills” condition based on qualifying client or related records.
Subs. Use Ref. Made?	Indicates whether the client satisfies the “Subs. Use referral Made” condition based on qualifying client or related records.
Subs. Use Relap. Prev. Discd?	Indicates whether the client satisfies the “Subs. Use Relap. Prev. Discd” condition based on qualifying client or related records.

Field Name	Description
Subs. Use Tr. 12 Step?	Indicates whether the client satisfies the “Subs. Use treatment 12 Step” condition based on qualifying client or related records.
Subs. Use Tr. Detox. Unit?	Indicates whether the client satisfies the “Subs. Use treatment Detox. Unit” condition based on qualifying client or related records.
Subs. Use Tr. Metha.?	Indicates whether the client satisfies the “Subs. Use treatment Metha.” condition based on qualifying client or related records.
Subs. Use Tr. Other Treat.?	Indicates whether the client satisfies the “Subs. Use treatment Other Treat.” condition based on qualifying client or related records.
Subs. Use Tr. Out Pat.?	Indicates whether the client satisfies the “Subs. Use treatment Out Pat.” condition based on qualifying client or related records.
Subs. Use Tr. Resid.?	Indicates whether the client satisfies the “Subs. Use treatment Resid.” condition based on qualifying client or related records.
Subservice Count	Returns the number of qualifying records or items represented by “Subservice Count”. The count is record-based unless the field explicitly defines unduplicated clients.
Subservice Count by Funding	Returns the number of qualifying records or items represented by “Subservice Count by Funding”. The count is record-based unless the field explicitly defines unduplicated clients.
Subservice count by funding in date span	Returns the number of qualifying records or items represented by “Subservice count by funding in date span” within the configured Date From and Date Through span. The count is record-based unless the field explicitly defines unduplicated clients.
Subservice Count In Span	Returns the number of qualifying records or items represented by “Subservice Count In Span” within the configured Date From and Date Through span. The count is record-based unless the field explicitly defines unduplicated clients.
Subservice Group Count	Returns the number of qualifying records or items represented by “Subservice Group Count”. The count is record-based unless the field explicitly defines unduplicated clients.
Subservice total cost	Returns the sum of qualifying monetary values represented by “Subservice total cost”.
Subservice units	Returns the client-level subservice units, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Subservice visit count X days apart	Returns the number of qualifying records or items represented by “Subservice visit count X days apart”. The count is record-based unless the field explicitly defines unduplicated clients.
Substance Use Screening	Returns the client-level “Substance Use Screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Syphilis screening	Returns the client-level “Syphilis screening” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Systolic Change	Calculates the difference represented by “Systolic Change” between the selected earlier and later qualifying values.

Field Name	Description
TB Med Started	Returns the client-level tb medication started, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
TB Med Status	Returns the client-level tb medication status, using the client record or the most applicable related record selected by the field's date and subfilter criteria.
TB prophylaxis start date	Returns the tb prophylaxis start date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
TB Screening	Returns the client-level "TB Screening" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
TB treatment start date	Returns the tb treatment start date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Test Last Qualitative Lab Date	Returns the test last qualitative lab date from the client record or the qualifying related record selected by the field's date and subfilter criteria.
Tobacco Use Cur. Smoker?	Indicates whether the client satisfies the "Tobacco Use Cur. Smoker" condition based on qualifying client or related records.
Total ADAP Deductable/Copay	Returns the sum of qualifying monetary values represented by "Total ADAP Deductable/Copay".
Total ADAP Funded Dispense Fees	Returns the sum of qualifying monetary values represented by "Total ADAP Funded Dispense Fees".
Total ADAP Part D Payments	Returns the sum of qualifying monetary values represented by "Total ADAP Part D Payments".
Total ADAP Premium Paid	Returns the sum of qualifying monetary values represented by "Total ADAP Premium Paid".
Total service visits	Returns the number of qualifying service or appointment records represented by "Total service visits", after applying service-category, subservice, funding, and interval criteria.
Toxoplasma Screening	Returns the client-level "Toxoplasma Screening" value from the client record or qualifying related records, according to the field's date, code, provider, funding, and subfilter settings.
Transferred in	Indicates whether the client satisfies the "Transferred in" condition based on qualifying client or related records.
Transferred in Agency	Indicates whether the client satisfies the "Transferred in Agency" condition based on qualifying client or related records.
Transferred out	Indicates whether the client satisfies the "Transferred out" condition based on qualifying client or related records.
Transfusion HIV risk	Indicates whether non-hemophilia blood transfusion is selected as an HIV risk factor for the client.
Transgender (All)	Returns the client-level transgender (all), using the client record or the most applicable related record selected by the field's date and subfilter criteria.
Transgender Status	Displays the client's transgender-status value.
Transgender Type	Displays the specific transgender type selected for the client.

Field Name	Description
Trimester entered Care-RDR	Returns the client-level “Trimester entered Care-RDR” result using the applicable CAREWare program-reporting logic and the qualifying demographic, clinical, enrollment, insurance, or service records.
Trnsfr Out Agency	Returns the client-level “Trnsfr Out Agency” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
TST Indicated	Returns the client-level “TST Indicated” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
TST Indicated For Period	Returns the client-level “TST Indicated For Period” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Two Primary Care visits>= 3mos Apart	Returns the number of qualifying service or appointment records represented by “Two Primary Care visits>= 3mos Apart”, after applying service-category, subservice, funding, and interval criteria.
Units of CARE Act Funded Services by Category	Returns the client-level units of care act funded services by category, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Units of Service by Category	Returns the client-level units of service by category, using the client record or the most applicable related record selected by the field’s date and subfilter criteria.
Unknown	Indicates whether the applicable client value is recorded as unknown for the field’s reporting definition.
Unknown HIV risk	Indicates whether the client’s HIV risk factor is recorded as undetermined or unknown.
Unknown race	Indicates whether the client’s race is recorded as unknown.
URN	Displays the client’s unique record number.
VA, Tricare and other military health care	Returns the client-level “VA, Tricare and other military health care” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Vietnamese	Indicates whether Vietnamese is selected for the client’s Asian subgroup.
Visits by service category in date span	Returns the number of qualifying service or appointment records represented by “Visits by service category in date span” within the configured Date From and Date Through span, after applying service-category, subservice, funding, and interval criteria.
Vital Status	Displays the client’s vital-status value.
Vital status by end date	Returns the latest applicable vital status on or before the configured key date or report Date Through.
Vital status by key date	Returns the latest applicable vital status on or before the configured key date or report Date Through.
weight At ART	Returns the client-level weight at art selected or calculated from qualifying vital-sign, lab, or screening records.

Field Name	Description
Weight At ART (kg)	Returns the client-level weight at art (kg) selected or calculated from qualifying vital-sign, lab, or screening records.
Weight Percent Change	Calculates the percentage or rate represented by “Weight Percent Change” from the qualifying numerator and denominator values defined by the field and its date criteria.
White race	Indicates whether White is selected for the client’s race.
WHO Stage At ART	Returns the client-level “WHO Stage At ART” value from the client record or qualifying related records, according to the field’s date, code, provider, funding, and subfilter settings.
Year of AIDS diagnosis	Returns the calendar year from the client’s AIDS diagnosis date.
Zip code	Displays the ZIP code recorded for the client’s residence.

Diagnosis

One row represents a diagnosis record. Diagnosis labels, assessments, statuses, and code descriptions may be resolved from linked reference and coding records.

Date behavior: Diagnosis Date.

Field Name	Description
Assessment	Displays the diagnosis assessment value, such as definitive, presumptive, or unknown, resolved from the diagnosis-assessment reference values.
Comment	Displays the comment entered for the diagnosis record.
Date Resolved	Displays the date and time the problem diagnosis was marked resolved.
Diagnosis Date	Displays the date of the diagnosis. This is the critical date used to include diagnosis rows within the report date span.
Diagnosis Details	Displays the user-defined diagnosis or problem text associated with the diagnosis record.
Diagnosis Has Code	Indicates whether the diagnosis record has at least one mapped diagnosis code.
Diagnosis Provider	Displays the provider domain associated with the diagnosis record.
ICD10 Code	Displays the ICD-10 code mapped to the diagnosis record.
ICD10 Description	Displays the description associated with the mapped ICD-10 code.
ICD10CM	Displays the ICD-10-CM code value associated with the diagnosis record.
ICD9	Displays the ICD-9 code associated with the selected diagnosis definition.
ICD9 Diagnosis	Displays the diagnosis label associated with the ICD-9-based diagnosis definition.
ICD9 Diagnosis Code	Displays the ICD-9 code mapped to the diagnosis record or diagnosis definition.
ICD9 Diagnosis Description	Displays the description associated with the mapped ICD-9 diagnosis code.
Status	Displays the problem-status value assigned to the diagnosis record.

Drug Service

One row represents an ADAP drug service or dispensed-drug transaction and may join formulary, NDC, generic drug, funding, payment, and dispenser details.

Date behavior: Drug Service Date.

Field Name	Description
ADAP Formulary Active Date	Displays the date the ADAP formulary item was activated.
ADAP Formulary Dispensing Fee	Displays the dispensing fee configured for the ADAP formulary item.
ADAP Formulary Indication	Displays the ADAP indication linked to the formulary item.
ADAP Formulary Requires Protocol	Indicates whether the ADAP formulary item requires a protocol.
ADAP Formulary Unit Price	Displays the unit price configured for the ADAP formulary item.
ADAP Generic Drug	Displays the generic drug name linked to the ADAP formulary or NDC record.
ADAP Med Count Baby	Returns the medication count used by the ADAP reporting calculation identified by this field.
ADAP medication brand Name	Displays the brand medication name linked to the ADAP NDC record.
ADAP NDC	Displays the National Drug Code associated with the ADAP formulary item.
ADAP NDC Manufacturer	Displays the manufacturer associated with the ADAP National Drug Code.
ADAP NDC Package Size	Displays the package size associated with the ADAP National Drug Code.
ADAP NDC Strength	Displays the medication strength associated with the ADAP National Drug Code.
ADR Client Defined Drug	Indicates or identifies the client-defined drug value used for ADR reporting.
ADR Drug Code	Displays the drug code used for ADR reporting.
Drug Payment Duration	Displays the number of days associated with the drug payment or formulary duration.
Drug Service Date	Displays the date of the drug service or dispensing transaction. This is the critical date used to include drug-service rows within the report date span.
Drug Service Dispense Fee	Displays the dispensing fee recorded for the drug-service transaction.
Drug Service Dispenser Contact	Displays the contact person recorded for the dispenser.
Drug Service Dispenser Name	Displays the name of the dispenser associated with the drug-service transaction.
Drug Service Dispenser Notes	Displays the notes recorded for the dispenser or drug-service transaction.
Drug Service Dispenser Phone	Displays the phone number recorded for the dispenser.
Drug Service Drug Cost	Displays the drug cost recorded for the transaction before or apart from other fees.
Drug Service Funding	Displays the funding source associated with the drug-service transaction.
Drug Service Last Updated	Displays the date and time the drug-service record was last updated.
Drug Service Quantity	Displays the quantity of units dispensed or prescribed for the transaction.

Field Name	Description
Drug Service Total	Displays the stored transaction total associated with the dispensed quantity and price.
Drug Service Total Cost	Displays the total cost of the drug-service transaction, including the components used by the applicable ADAP calculation.

Eligibility

One row represents an eligibility determination, linked to the client, provider domain, funding source, and eligibility status.

Date behavior: Eligibility Date.

Field Name	Description
Eligibility Date	Displays the date of the eligibility determination. This is the critical date used to include eligibility rows within Date From and Date Through.
Eligibility End Date	Displays the ending date associated with the eligibility period or status when the selected eligibility configuration supplies an end date.
Eligibility Funding Source	Displays the funding source linked to the eligibility determination.
Eligibility Status	Displays the Yes/No eligibility determination recorded for the funding source and date.

Immunization

One row represents an immunization record, with vaccine definitions and code mappings used to resolve names, CVX values, and related attributes.

Date behavior: Vaccine Date.

Field Name	Description
Amount Administered	Displays the amount of vaccine administered for the immunization record.
CVX	Displays the CVX code associated with the selected immunization definition.
ImmCVX	Displays the CVX value stored or mapped for the immunization record.
Immunity	Displays the immunity or immunization-history status associated with the record.
Immunization Has Code	Indicates whether the immunization record has at least one mapped immunization code.
Immunization Provider	Displays the provider domain associated with the immunization record.
Lot Number	Displays the manufacturer lot number recorded for the administered vaccine.
Manufacturer Code	Displays the manufacturer code recorded for the administered vaccine.
Manufacturer Name	Displays the manufacturer name recorded for the administered vaccine.
Received Immunization	Indicates whether the record represents an immunization that was received.
Series Number	Displays the dose or series number associated with the immunization record.
Units Administered	Displays the unit of measure recorded for the administered amount.
Vaccine date	Displays the date of the immunization. This is the critical date used to include immunization rows within the report date span.

Field Name	Description
Vaccine name	Displays the user-facing vaccine name resolved from the immunization definition.
Vaccine updated	Displays the update-status value associated with the immunization record.

Insurance Assessment

One row represents an insurance assessment. Coverage flags, primary coverage, codes, and descriptive values are read from the assessment and linked insurance reference records.

Date behavior: Insurance Assessment Date.

Field Name	Description
All Insurance Codes	Displays the combined insurance codes associated with the assessment.
FullLis	Indicates whether the insurance assessment records full Low-Income Subsidy coverage.
In High Risk Pool	Indicates whether the client was recorded as participating in a high-risk insurance pool on the assessment.
Insurance Assessment Date	Displays the date of the client's insurance assessment. This is the critical date used to include assessment rows within the report date span.
Insurance Has Association Plan	Indicates whether an association-plan coverage type was selected on the assessment.
Insurance Has High Risk Insurance	Indicates whether high-risk insurance coverage was selected on the assessment.
Insurance Has Indian Health Service	Indicates whether Indian Health Service coverage was selected on the assessment.
Insurance Has Medicaid, CHIP or Other Public Plan	Indicates whether Medicaid, CHIP, or another public-plan coverage type was selected on the assessment.
Insurance Has Medicare (unspecified)	Indicates whether unspecified Medicare coverage was selected on the assessment.
Insurance Has Medicare Part A/B	Indicates whether Medicare Part A or Part B coverage was selected on the assessment.
Insurance Has Medicare Part C	Indicates whether Medicare Part C coverage was selected on the assessment.
Insurance Has Medicare Part D	Indicates whether Medicare Part D coverage was selected on the assessment.
Insurance Has No Insurance	Indicates whether the assessment records the client as having no insurance coverage.
Insurance Has Other Plan	Indicates whether an other-plan coverage type was selected on the assessment.
Insurance Has Other public (e.g. Champus, VA)	Indicates whether another public coverage type, such as CHAMPUS or VA coverage, was selected on the assessment.
Insurance Has Private - Employer	Indicates whether employer-sponsored private insurance was selected on the assessment.
Insurance Has Private - Individual	Indicates whether individually purchased private insurance was selected on the assessment.

Field Name	Description
Insurance Has Private (Deprecated)	Indicates whether the legacy private-insurance flag was selected on the assessment. Use current private-employer or private-individual fields for newer reporting designs.
Insurance Has Unknown	Indicates whether insurance coverage was recorded as unknown on the assessment.
Insurance Has VA, Tricare and other military health care	Indicates whether VA, TRICARE, or other military health coverage was selected on the assessment.
Other Insurance Assessment Description	Displays the user-entered description for an other-insurance selection.
Primary Insurance Assessment	Displays the primary insurance type assigned to the assessment.
Primary Insurance Code	Displays the code associated with the primary insurance selection.
Secondary Insurance Codes	Displays the combined codes associated with secondary insurance selections.

Lab

One row represents a lab test record. Test definitions, assays, result values, code mappings, data source, status, and provider may be joined to the test record.

Date behavior: Lab Date.

Field Name	Description
Lab =?	Displays the configured comparison or interpretation associated with the lab result.
Lab Ascension Number	Displays the accession or ascension identifier used to distinguish the imported or entered lab test.
Lab Assay	Displays the assay associated with the lab test.
Lab Comment	Displays the comment entered for the lab test record.
Lab Data Source	Displays the source of the lab data, including an imported source when supplied by an interface.
Lab Date	Displays the date of the lab test. This is the critical date used to include lab rows within the report date span.
Lab Has Code	Indicates whether the lab test has at least one mapped lab code.
Lab Result	Displays the recorded qualitative or quantitative lab result, formatted according to the test definition.
Lab Status	Displays the status recorded for the lab test, including interface-supplied status values when applicable.
Lab System	Displays the coding system associated with the lab code.
Lab Test	Displays the user-facing lab test name resolved from the test definition.
Lab Test For Reporting	Displays the reporting test definition linked to the entered lab test when CAREWare maps multiple test definitions to a common reporting test.
Test Provider	Displays the provider domain associated with the lab test record.

Medication

One row represents a client medication record, linked to medication definitions, frequency, indication, prophylaxis, coding, form, and provider values.

Date behavior: Medication Start Date and Stop Date.

Field Name	Description
Comment	Displays the comment recorded for the medication entry.
Daily Dose	Displays the total daily dose calculated from the medication strength and frequency.
Dose	Displays the dose recorded for the medication entry.
Frequency	Displays the medication frequency resolved from the frequency reference values.
HRSA Code	Displays the HRSA-related medication code associated with the medication definition or code mapping.
Indication	Displays the clinical indication associated with the medication entry.
IndicationRPK	Displays the internal reference key for the medication indication; use it for technical reconciliation rather than as a user-facing label.
Instructions	Displays the medication instructions entered for the client.
Med ICD 10	Displays the ICD-10 code linked to the medication entry.
Med ICD 10 Description	Displays the description associated with the medication's linked ICD-10 code.
Medication	Displays the user-facing medication name resolved from the available-medication record.
Medication Form	Displays the medication form linked to the entry, such as the configured pediatric or dosage form.
Medication Has Code	Indicates whether the medication entry has at least one mapped medication code.
Medication Provider	Displays the provider domain associated with the medication entry.
OI name	Displays the opportunistic-infection indication or prophylaxis name associated with the medication entry.
Start Date	Displays the medication start date. Medication reports evaluate start and stop dates against the report date span.
Stop Date	Displays the medication end or stop date. Medication reports evaluate start and stop dates against the report date span.
Stop Reason	Displays the reason the medication was discontinued, resolved from the discontinue-reason reference values.
Strength	Displays the medication strength recorded for the entry, with units determined by the medication configuration.
Units	Displays the medication units recorded for the entry.

Parent

One row represents a relationship link and displays attributes from the client identified as the parent or index side of that link.

Date behavior: Relations behavior; Service Date is identified for the Relations report type in CAREWare guidance.

Field Name	Description
Relation AIDS diagnosis date	Displays the AIDS diagnosis date for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation date case closed	Displays the date the related client's case or enrollment was closed for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation date of birth	Displays the date of birth for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation date of death	Displays the date of death for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation enroll date	Displays the provider enrollment date for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation enroll status	Displays the provider enrollment status for the client on the parent or index side of the relationship, resolved from the applicable client or provider-enrollment reference value.
Relation eURN	Displays the encrypted or extended unique record number for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation first name	Displays the first name for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation gender	Displays the gender for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation HIV diag date	Displays the HIV diagnosis date for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation last name	Displays the last name for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation middle name	Displays the middle name for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation type	Displays the relationship type that links the index client and dependent client, resolved from the relationship reference values.
Relation URN	Displays the unique record number for the client on the parent or index side of the relationship by joining the relationship link to that client's record.
Relation vital status	Displays the vital status for the client on the parent or index side of the relationship, resolved from the applicable client or provider-enrollment reference value.

Poverty Level Assessment

One row represents a poverty level assessment containing household income, household size, individual income, and the calculated federal poverty level.

Date behavior: Poverty Level Assessment Date.

Field Name	Description
House Hold Income Assessment	Displays the household income amount recorded on the poverty level assessment.
House Hold Size Assessment	Displays the household size recorded on the poverty level assessment.
Individual Income	Displays the individual income amount recorded on the poverty level assessment.
Poverty Level Assessment	Displays the calculated federal poverty level percentage stored for the assessment.
Poverty Level Assessment Date	Displays the date of the recorded poverty level information. This is the critical date used to include assessment rows within the report date span.

Pregnancy History

One row represents a pregnancy history record, including conception, prenatal care, antiretroviral use, outcome, delivery, newborn status, and provider values.

Date behavior: Pregnancy Date, generally the estimated conception date.

Field Name	Description
Conception date	Displays the estimated conception date recorded for the pregnancy. This generally serves as the pregnancy-history reference date.
Delivery Date	Displays the delivery date recorded when the pregnancy outcome involved a birth.
Newborn HIV status	Displays the newborn HIV-status reference value linked to the pregnancy outcome.
Number prenatal visits	Displays the number of prenatal visits recorded for the pregnancy.
Offered prenatal ART	Indicates whether antiretroviral therapy was offered during the pregnancy to reduce maternal HIV transmission risk.
Pregnancy History Provider	Displays the provider domain associated with the pregnancy-history record.
Pregnancy outcome	Displays the pregnancy-outcome value resolved from the pregnancy-outcome reference values.
Prenatal ART start date	Displays the date prenatal antiretroviral therapy started for the pregnancy.
Prenatal ART taken	Indicates whether the client took antiretroviral therapy during the pregnancy to reduce maternal HIV transmission risk.
Prenatal care start date	Displays the date prenatal care began for the pregnancy.
Prenatal counseling	Indicates whether the provider counseled the client during the pregnancy about preventing maternal HIV transmission.

Referrals

One row represents a referral. Provider, service category, definition, class, type, status, code, user, and received-service relationships may supply display values.

Date behavior: Referral Date.

Field Name	Description
Received Date	Displays the date the referred service was received.
Referral Class	Displays the referral class linked to the referral record.
Referral Comment	Displays the referral comment, including the referred-to organization name for an external referral when entered there.
Referral Created By User	Displays the user associated with creating the referral record.
Referral Data Entry Date Difference	Calculates the number of days between the referral date and the date the referral record was entered or created.
Referral Date	Displays the date the referral was made. This is the critical date used to include referral rows within the report date span.
Referral Definition by Sponsor	Displays the sponsor-specific referral definition linked through the referral's service or configuration.
Referral Has Code	Indicates whether the referral record has at least one mapped referral code.
Referral service category	Displays the service category associated with the referral.
Referral Status	Displays the current status assigned to the referral.
Referral Status Updated By User	Displays the user associated with the most recent referral-status update.
Referral Type	Displays whether the referral is internal or external, resolved from the referral-type reference values.
Referred by Provider	Displays the provider domain from which the referral originated.
Referred To Provider	Displays the internal provider domain or external provider to which the client was referred.

Relations

One row represents a relationship link between an index client and a dependent client, with the relationship type and related-client attributes resolved through linked records.

Date behavior: Service Date, as identified for the Relations report type in CAREWare guidance.

Field Name	Description
Relation AIDS diagnosis date	Displays the AIDS diagnosis date for the related client in the relationship by joining the relationship link to that client's record.
Relation date case closed	Displays the date the related client's case or enrollment was closed for the related client in the relationship by joining the relationship link to that client's record.
Relation date of birth	Displays the date of birth for the related client in the relationship by joining the relationship link to that client's record.
Relation date of death	Displays the date of death for the related client in the relationship by joining the relationship link to that client's record.

Field Name	Description
Relation enroll date	Displays the provider enrollment date for the related client in the relationship by joining the relationship link to that client's record.
Relation enroll status	Displays the provider enrollment status for the related client in the relationship, resolved from the applicable client or provider-enrollment reference value.
Relation eURN	Displays the encrypted or extended unique record number for the related client in the relationship by joining the relationship link to that client's record.
Relation first name	Displays the first name for the related client in the relationship by joining the relationship link to that client's record.
Relation gender	Displays the gender for the related client in the relationship by joining the relationship link to that client's record.
Relation HIV diag date	Displays the HIV diagnosis date for the related client in the relationship by joining the relationship link to that client's record.
Relation last name	Displays the last name for the related client in the relationship by joining the relationship link to that client's record.
Relation middle name	Displays the middle name for the related client in the relationship by joining the relationship link to that client's record.
Relation type	Displays the relationship type that links the index client and dependent client, resolved from the relationship reference values.
Relation URN	Displays the unique record number for the related client in the relationship by joining the relationship link to that client's record.
Relation vital status	Displays the vital status for the related client in the relationship, resolved from the applicable client or provider-enrollment reference value.

ROI Agreement

One row represents a release-of-information agreement, including its active period, provider domain, and sharing type.

Date behavior: ROI Start Date and ROI End Date.

Field Name	Description
ROI Active	Indicates whether the release-of-information agreement is marked active.
ROI End Date	Displays the ending date of the release-of-information authorization period.
ROI Provider	Displays the provider domain associated with the release-of-information agreement.
ROI Share Type	Displays the sharing type assigned to the release-of-information agreement.
ROI Start Date	Displays the starting date of the release-of-information authorization period.

Screening

One row represents a screening test record. Screening definitions, actions, results, scores, status, code mappings, data source, and provider may be joined to the test record.

Date behavior: Screening Date.

Field Name	Description
Screening Action	Displays the action associated with the screening result, resolved from the configured screening action values.
Screening Ascension Number	Displays the accession or ascension identifier used to distinguish the imported or entered screening test.
Screening Comment	Displays the comment entered for the screening record.
Screening Data Source	Displays the source of the screening data, including an imported source when supplied by an interface.
Screening Date	Displays the date of the screening test. This is the critical date used to include screening rows within the report date span.
Screening Has Code	Indicates whether the screening record has at least one mapped screening code.
Screening Result	Displays the recorded screening result, formatted according to the test definition.
Screening Score	Displays the numeric score recorded for the screening test.
Screening Status	Displays the status recorded for the screening test.
Screening Test	Displays the user-facing screening test name resolved from the test definition.
Test Provider	Displays the provider domain associated with the screening record.

Screening Lab

One row represents a screening-lab test record. Test definitions, qualitative or titer results, treatment, STI action, code mappings, source, and provider may supply report values.

Date behavior: Screening Lab Date.

Field Name	Description
Screening lab result	Displays the recorded qualitative, quantitative, or coded result for the screening-lab test.
Screening lab comment	Displays the comment entered for the screening-lab record.
Screening lab date	Displays the screening-lab test date. This is the critical date used to include screening-lab rows within the report date span.
Screening Lab Has Code	Indicates whether the screening-lab record has at least one mapped screening-lab code.
Screening lab status	Displays the status recorded for the screening-lab test.
Screening lab test name	Displays the user-facing screening-lab test name resolved from the test definition.
Screening lab titer	Displays the titer value recorded for a screening-lab test configured to use titers.

Field Name	Description
Screening lab treatment	Displays the treatment associated with the screening-lab result.
ScrLab Data Source	Displays the source of the screening-lab data, including an imported source when supplied by an interface.
ScrLab Ascension Number	Displays the accession or ascension identifier used to distinguish the imported or entered screening-lab test.
STI Action	Displays the action associated with a sexually transmitted infection screening-lab result.
Test Provider	Displays the provider domain associated with the screening-lab record.

Service

One row represents a service record, linked to subservice, service category, contract, sponsor, funding, provider, code, tag, billing, and user records.

Date behavior: Service Date.

Field Name	Description
Billing 2nd Ins. ID	Displays the secondary insured identifier recorded for billing on the service or linked insurance assessment.
Billing CPT Code	Displays the CPT procedure code used for billing the service.
Billing CPT Location	Displays the service-location value associated with the billing CPT information.
Billing CPT Modifier	Displays the CPT modifier recorded for the service billing entry.
Billing CPT Rate	Displays the billing rate associated with the CPT code for the service.
Billing Dgn Code	Displays the diagnosis code recorded for billing the service.
Billing End Time	Displays the billing end time recorded for the service.
Billing Ins. ID	Displays the primary insured identifier recorded for billing.
Billing Insurance	Displays the insurance selection used for billing the service.
Billing Insurer	Displays the billing insurer linked to the service or insurance assessment.
Billing Insurer City	Displays the city recorded for the billing insurer.
Billing Insurer Code	Displays the configured code for the billing insurer.
Billing Insurer NPI	Displays the National Provider Identifier recorded for the billing insurer.
Billing Insurer Payer ID	Displays the payer identifier recorded for the billing insurer.
Billing Insurer State	Displays the state recorded for the billing insurer.
Billing Insurer Street	Displays the street address recorded for the billing insurer.
Billing Insurer Suite	Displays the suite or secondary address line recorded for the billing insurer.
Billing Insurer UseNPIS	Indicates whether the billing insurer configuration uses National Provider Identifier values.
Billing Insurer UseProviderID	Indicates whether the billing insurer configuration uses provider identifiers.
Billing Insurer Zip	Displays the ZIP code recorded for the billing insurer.

Field Name	Description
Billing Provider	Displays the employee or provider associated with billing the service.
Billing Start Time	Displays the billing start time recorded for the service.
Billing Units	Displays the number of units used for billing the service.
Contract Item	Displays the contract item linked through the service's subservice and contract configuration.
Created By	Displays the user or employee associated with creating the service record.
Effective Date	Displays the effective date associated with the selected contract, rate, or service configuration.
Ins. Initials	Displays the initials recorded for the insurance or billing entry.
Is Billable	Indicates whether the service is marked as billable.
Last Updated By	Displays the user associated with the most recent update to the service record.
Primary health service	Indicates whether the service is classified as a primary health service under the applicable CAREWare reporting definition.
Recipient ID	Displays the recipient identifier associated with the service or billing record.
RSR Service Is RW Eligible	Indicates whether the service meets CAREWare's Ryan White eligibility logic for RSR service reporting.
RW-funded visits by service category	Returns the number of Ryan White-funded service visits in the selected service category and configured date span.
Service category	Displays the service category linked to the service's subservice definition.
Service category primary key	Displays the internal key for the service category; use it for technical reconciliation rather than as a user-facing category name.
Service contract	Displays the contract linked to the service record.
Service Data Entry Date Difference	Calculates the number of days between the service date and the date the service record was entered or created.
Service date	Displays the date the service was provided. This is the critical date used to include service rows within the report date span.
Service Date Created	Displays the database timestamp recorded when the service record was created.
Service definition by sponsor	Displays the sponsor-specific service definition linked to the service.
Service funding source	Displays the funding source associated with the service through its contract or service configuration.
Service Has Code	Indicates whether the service has at least one mapped service code.
Service Has Funding	Indicates whether the service is linked to a funding source.
Service Has Tag	Indicates whether the service or subservice has the selected tag.
Service name	Displays the user-facing subservice or service-definition name for the service record.
Service Primary Key	Displays the internal unique identifier for the service record; use it for technical reconciliation or joins.

Field Name	Description
Service Provider	Displays the provider domain associated with the service record.
Service received	Indicates whether the service record meets the selected received-service condition.
Service RW funded	Indicates whether the service is funded by a Ryan White funding source.
Service sponsor	Displays the sponsor associated with the contract or service configuration.
Service total	Displays the stored total amount for the service record.
Service unit price	Displays the unit price recorded for the service.
Service units	Displays the quantity or number of units recorded for the service.
Service User	Displays the user name stored with the service record.
Service visits by category	Returns the number of service visits in the selected service category and configured date span.
Srv Long Name	Displays the long name of the service or subservice definition.
Subservice name	Displays the subservice name linked to the service record.
Subservice Tags	Displays the tags assigned to the subservice linked to the service.
Subservice Total (STRMU)	Returns the subservice total used for HOPWA Short-Term Rent, Mortgage, and Utility reporting.
Subservice Total (TBRA)	Returns the subservice total used for HOPWA Tenant-Based Rental Assistance reporting.

Service Receipts

One row represents a receipt linked to a service record, so receipt values can be reported with the service, contract, funding, provider, billing, and subservice details.

Date behavior: Receipt Date.

Field Name	Description
Billing 2nd Ins. ID	Displays the secondary insured identifier recorded for billing on the service or linked insurance assessment.
Billing CPT Code	Displays the CPT procedure code used for billing the service.
Billing CPT Location	Displays the service-location value associated with the billing CPT information.
Billing CPT Modifier	Displays the CPT modifier recorded for the service billing entry.
Billing CPT Rate	Displays the billing rate associated with the CPT code for the service.
Billing Dgn Code	Displays the diagnosis code recorded for billing the service.
Billing End Time	Displays the billing end time recorded for the service.
Billing Ins. ID	Displays the primary insured identifier recorded for billing.
Billing Insurance	Displays the insurance selection used for billing the service.
Billing Insurer	Displays the billing insurer linked to the service or insurance assessment.
Billing Insurer City	Displays the city recorded for the billing insurer.

Field Name	Description
Billing Insurer Code	Displays the configured code for the billing insurer.
Billing Insurer NPI	Displays the National Provider Identifier recorded for the billing insurer.
Billing Insurer Payer ID	Displays the payer identifier recorded for the billing insurer.
Billing Insurer State	Displays the state recorded for the billing insurer.
Billing Insurer Street	Displays the street address recorded for the billing insurer.
Billing Insurer Suite	Displays the suite or secondary address line recorded for the billing insurer.
Billing Insurer UseNPIS	Indicates whether the billing insurer configuration uses National Provider Identifier values.
Billing Insurer UseProviderID	Indicates whether the billing insurer configuration uses provider identifiers.
Billing Insurer Zip	Displays the ZIP code recorded for the billing insurer.
Billing Provider	Displays the employee or provider associated with billing the service.
Billing Start Time	Displays the billing start time recorded for the service.
Billing Units	Displays the number of units used for billing the service.
Contract Item	Displays the contract item linked through the service's subservice and contract configuration.
Created By	Displays the user or employee associated with creating the service record.
Effective Date	Displays the effective date associated with the selected contract, rate, or service configuration.
Ins. Initials	Displays the initials recorded for the insurance or billing entry.
Is Billable	Indicates whether the service is marked as billable.
Last Updated By	Displays the user associated with the most recent update to the service record.
Out Of pocket Expense	Indicates whether the receipt amount is recorded as an out-of-pocket expense.
Primary health service	Indicates whether the service is classified as a primary health service under the applicable CAREWare reporting definition.
Receipt Amount	Displays the monetary amount received for the service receipt.
Receipt Date	Displays the date of the receipt. This is the critical date used to include receipt rows within the report date span.
Receipt Source	Displays the person, organization, or source from which the payment was received.
Recipient ID	Displays the recipient identifier associated with the service or billing record.
RSR Service Is RW Eligible	Indicates whether the service meets CAREWare's Ryan White eligibility logic for RSR service reporting.
RW-funded visits by service category	Returns the number of Ryan White-funded service visits in the selected service category and configured date span.
Service category	Displays the service category linked to the service's subservice definition.
Service category primary key	Displays the internal key for the service category; use it for technical reconciliation rather than as a user-facing category name.

Field Name	Description
Service contract	Displays the contract linked to the service record.
Service Data Entry Date Difference	Calculates the number of days between the service date and the date the service record was entered or created.
Service date	Displays the date the service was provided. This is the critical date used to include service rows within the report date span.
Service Date Created	Displays the database timestamp recorded when the service record was created.
Service definition by sponsor	Displays the sponsor-specific service definition linked to the service.
Service funding source	Displays the funding source associated with the service through its contract or service configuration.
Service Has Code	Indicates whether the service has at least one mapped service code.
Service Has Funding	Indicates whether the service is linked to a funding source.
Service Has Tag	Indicates whether the service or subservice has the selected tag.
Service name	Displays the user-facing subservice or service-definition name for the service record.
Service Primary Key	Displays the internal unique identifier for the service record; use it for technical reconciliation or joins.
Service Provider	Displays the provider domain associated with the service record.
Service received	Indicates whether the service record meets the selected received-service condition.
Service RW funded	Indicates whether the service is funded by a Ryan White funding source.
Service sponsor	Displays the sponsor associated with the contract or service configuration.
Service total	Displays the stored total amount for the service record.
Service unit price	Displays the unit price recorded for the service.
Service units	Displays the quantity or number of units recorded for the service.
Service User	Displays the user name stored with the service record.
Service visits by category	Returns the number of service visits in the selected service category and configured date span.
Srv Long Name	Displays the long name of the service or subservice definition.
Subservice name	Displays the subservice name linked to the service record.
Subservice Tags	Displays the tags assigned to the subservice linked to the service.
Subservice Total (STRMU)	Returns the subservice total used for HOPWA Short-Term Rent, Mortgage, and Utility reporting.
Subservice Total (TBRA)	Returns the subservice total used for HOPWA Tenant-Based Rental Assistance reporting.

Vital Signs

One row represents a vital-sign encounter containing date, height, weight, pulse, blood pressure, temperature, provider, and calculated BMI values.

Date behavior: Vitals Date.

Field Name	Description
Body Mass Index	Returns body mass index calculated from the height and weight recorded for the vital-sign encounter.
BP(sys/dia)	Displays the systolic and diastolic blood-pressure values together for the vital-sign encounter.
Diastolic BP	Displays the diastolic blood-pressure value recorded for the vital-sign encounter.
ER Visits	Returns the number of emergency-room visits associated with the selected client and reporting criteria.
Height(cm)	Displays the recorded height converted or formatted in centimeters.
Height(in)	Displays the recorded height converted or formatted in inches.
Hosp/ER Reason	Displays the reason associated with a hospital or emergency-room event when available from the related record.
Hospital days	Returns the number of hospital days associated with the selected client and reporting criteria.
Hospital visits	Returns the number of hospital visits associated with the selected client and reporting criteria.
Pulse(bpm)	Displays the pulse recorded in beats per minute for the vital-sign encounter.
Systolic	Displays the systolic blood-pressure value recorded for the vital-sign encounter.
Temp(◆f)	Displays the recorded body temperature converted or formatted in degrees Fahrenheit.
Temp°C	Displays the recorded body temperature converted or formatted in degrees Celsius.
Vital Signs Provider	Displays the provider domain associated with the vital-sign encounter.
Vitals Date	Displays the date the client's vital signs were taken. This is the critical date used to include vital-sign rows within the report date span.
Weight(kg)	Displays the recorded weight converted or formatted in kilograms.
Weight(lbs)	Displays the recorded weight converted or formatted in pounds.

Subfilter Field

These entries are configuration parameters used by report filters that require a subfilter. They select codes, date spans, comparison values, providers, services, or sequence rules rather than defining a report row.

Date behavior: Not applicable; the parent filter and its date or key-date settings control evaluation.

Filter Parameter	Description
ADAP DisEnroll Reason	Selects the ADAP disenrollment-reason value that the parent filter must match.

Filter Parameter	Description
Any Test	Specifies that the parent filter may evaluate any qualifying test rather than one selected test definition.
Client primary key	Supplies the client's internal unique identifier for a technical subfilter comparison or join.
Contract	Selects the contract that related service records must use.
Contract Item	Selects the contract item that related service records must use.
Contract Item By Name	Selects a contract item by its displayed name rather than by an internal identifier.
Cross Provider Labs	Controls whether qualifying lab records from other permitted provider domains are considered.
Cross-Provider	Controls whether qualifying records from other permitted provider domains are considered by the parent filter.
Date Range	Sets the beginning and ending dates used to evaluate related records for the parent filter.
Date Span	Sets the date interval used to evaluate related records for the parent filter.
Date Span (Optional)	Provides an optional date interval that narrows the related records evaluated by the parent filter.
DateColumn	Selects which date field on the related record is compared with the configured date criteria.
Days Span	Sets the number of days included in the interval evaluated by the parent filter.
Diagnosis Code	Selects the diagnosis code that a related diagnosis record must contain.
Diagnosis Code System	Selects the coding system used to interpret the diagnosis code.
Diff Type	Selects how a calculated difference is expressed, such as an absolute, percentage, or other configured difference type.
Direction	Selects whether the sequence or date comparison is evaluated before, after, increasing, decreasing, or according to the parent filter's supported direction values.
Drug Funding Source	Selects the funding source that qualifying drug-service or payment records must use.
Drug Grace Period	Sets the allowed number of days around the expected drug-service or medication interval.
Error running	Identifies the execution-error state used by the filter configuration for diagnostic handling.
Field Name	Selects the custom, form, service, or other dynamic field evaluated by the parent filter.
Field Value	Sets the value that the selected dynamic field must satisfy.
Form Date	Sets or selects the custom form date used by the parent filter.
Form Name	Selects the custom form design whose records are evaluated.
Funding Source	Selects the funding source that qualifying related records must use.

Filter Parameter	Description
Grace Period	Sets the allowed number of days around the date or interval required by the parent filter.
Haart Class	Selects the antiretroviral therapy class that qualifying medications or regimens must contain.
HOPWA Enroll Type	Selects the HOPWA enrollment type evaluated by the parent filter.
HOPWA Exit Type	Selects the HOPWA exit type evaluated by the parent filter.
HOPWA Funding Source	Selects the HOPWA funding source that qualifying records must use.
HOPWA Program	Selects the HOPWA program whose enrollment or service records are evaluated.
ICD 10	Selects the ICD-10 diagnosis value evaluated by the parent filter.
immunization Code	Selects the immunization code that a related immunization record must contain.
immunization Code System	Selects the coding system used to interpret the immunization code.
Interval Days	Sets the required number of days between qualifying events or records.
Key Date	Sets the reference date used for an as-of-date, before/after, age, status, or interval calculation.
Lab	Selects the lab test definition evaluated by the parent filter.
Lab Code	Selects the lab code that a related lab record must contain.
Lab Code System	Selects the coding system used to interpret the lab code.
Medication Code	Selects the medication code that a related medication record must contain.
Medication Code System	Selects the coding system used to interpret the medication code.
Months In Span	Sets the number of months included in the date interval evaluated by the parent filter.
Num Days Last	Sets the look-back period, in days, measured from the report's reference date.
Number of preceding immunizations	Sets how many qualifying immunization records must occur before the selected immunization or procedure.
Number of subsequent immunizations	Sets how many qualifying immunization records must occur after the selected immunization or procedure.
Preceding Immunization	Selects the immunization that must occur before another qualifying event.
Preceding Immunization Code	Selects the code for the immunization that must occur before another qualifying event.
Preceding Subservice	Selects the subservice that must occur before another qualifying service event.
Previous Service Code	Selects the service code that must occur before the current or subsequent qualifying service.
Provider Name	Selects the provider domain that qualifying related records must belong to.
Qualitative Result	Selects the qualitative test result that qualifying records must match.
Referral Code	Selects the referral code that a related referral record must contain.

Filter Parameter	Description
Referral Code System	Selects the coding system used to interpret the referral code.
Result	Sets the result value that qualifying test or screening records must match.
Result Code	Selects the coded result that qualifying test or screening records must contain.
Review Date	Sets the annual-review or other review date used by the parent filter.
Screening Code	Selects the screening code that a related screening record must contain.
Screening Code System	Selects the coding system used to interpret the screening code.
Screening Lab Code	Selects the screening-lab code that a related screening-lab record must contain.
Screening Lab Code System	Selects the coding system used to interpret the screening-lab code.
Service Category	Selects the service category that qualifying service records must belong to.
Service Code	Selects the service code that a related service record must contain.
Service Code System	Selects the coding system used to interpret the service code.
Srv. Cat (Optional)	Provides an optional service-category restriction for the parent filter.
STI	Selects the sexually transmitted infection test or condition evaluated by the parent filter.
STI Code	Selects the code associated with the sexually transmitted infection test or condition.
Subsequent Immunization	Selects the immunization that must occur after another qualifying event.
Subsequent Immunization Code	Selects the code for the immunization that must occur after another qualifying event.
Subsequent Service Code	Selects the service code that must occur after the current or preceding qualifying service.
Subsequent Subservice	Selects the subservice that must occur after another qualifying service event.
Subservice	Selects the subservice that qualifying service records must use.
SubserviceType	Selects the subservice type evaluated by the parent filter.
Tag	Selects the tag that qualifying service, subservice, custom form, or other tagged records must contain.
Test Class	Selects the class of test definitions evaluated by the parent filter.
Test Code	Selects the test code that a related test record must contain.
Test Name	Selects the test definition evaluated by the parent filter.
Threshold Days	Sets the number of days a result must remain above, below, or otherwise related to the configured threshold.
Threshold Operator	Selects the comparison operator used with the threshold value, such as greater than or less than.
Threshold Value	Sets the numeric or coded threshold used to evaluate qualifying records.
Translated Value	Sets or selects the standardized value produced after a source value is translated for comparison.

Filter Parameter	Description
Trigger Operator	Selects the comparison operator that determines when the parent filter's trigger condition is met.
Trigger Value	Sets the value that activates the parent filter's trigger condition.
Value	Sets the comparison value used by the parent filter.

Related CAREWare guides and resources

Resource	How it helps
Creating Custom Reports	Choose a report type, add field selections, add report filters, set parameters, and understand row grain and critical dates.
Custom Report Run Report	Understand Date From, Date Through, Clinical Review Year, provider grouping, sharing options, and how report parameters affect results.
Creating a Subfilter	Add and edit the additional criteria required by filters that support subfilters.