


MODINE OVERVIEW






- Racine, WI Headquarters
- \$2.0 Billion Sales
- 11,000 Employees
- Manufacturing Plants Worldwide
- 2,200 Engineering Patents
- Applied Thermal Innovation
- Recently Acquired Luvata Heat Transfer Solutions (Heatcraft Coils)









BUILDING HVAC SEGMENTS





Commercial Ventilation







HOT DAWG



Infrared Radiant













Commercial Hydronics







GUIDE TO EFFECTIVE GREENHOUSE HEATING





What We Will Cover Today:

- Maintenance Tips
- Heating Options
- Modine Advantages
- Heater Size and Location
- Energy Savings
- PTC 93% High Efficiency Unit Heater
- Payback Calculator



GREENHOUSE MAINTENANCE TIPS PREVENTATIVE MAINTENANCE





General Pre-season Maintenance

- Check equipment for any physical damage that may have occurred in the off-season. This should include damage to sheet metal, fans and air movers, wiring, gas piping, and vent system.
- Check for cleanliness of heat exchangers, burners, and burner orifices.
- For unit heaters with condensate lines, check for any damage or blockages in lines.
- Check to make certain vent system is clear.
 Sometimes birds like to take up residence in unused vent pipes.
- Check to make sure no obstructions block air inlet or air discharge of equipment.

GREENHOUSE MAINTENANCE TIPS PREVENTATIVE MAINTENANCE





General Pre-season Maintenance

- Ensure unit supports are secure and unit hangs level.
- Check and adjust gas pressures.
- Inspect and clean pilot assembly/flame sensors.
- Do a complete start up to ensure the proper operation from start to finish.
- For further instruction see Modine Preseason Checklist 76-500P.



STREET, SQUARE, AS NOT THE OWNER, THE PARTY NAMED IN COLUMN TWO IS NOT THE OWNER.

76-600P | October, 2017

WARNING: This work must be performed by a qualified service or maintenance technician.

CHECKLIST FOR KEEPING THE HEAT ON

GENERAL MAINTENANCE

- Check equipment for any physical damage that may have occured over the summer. This should include damage to sheet metal, fans and air movers, wiring, gas pipes, vent systems, and equipment supports.
- M Look for cleanliness of heat exchanger and burners.
- Check to make certain the vent system has not been compromised and is in the proper working order.
- Check for obstructions that may be blocking the air inlet or discharge paths of the heat exchanger.

GAS SUPPLY

Check to make sure that gas mains are turned on.

- Check inlet pressure and manifold gas pressure to heating equipment to make sure it is properly set.
- Check gas regulators to be certain regulator vents are
- If propere is being used, check main regulator on tanks for proper pressure settings and check for damage to regulators.
- Check propane tanks for proper size and liquid propane levels.

GAS CONTROLS

- Inspect all gas connections for good tight fits. This includes pipe connections to the equipment as well as pilot tubing connections at the gas valve and at the pilot burner.
- Inspect the main burner gas orifices to make sure they are not blocked with spider webs. Check pilot orifice for obstructions if pilot cannot be lit or will not stay lit.
- After visual and physical inspection of the gas connection, turn on the gas and check for gas leaks using a water/scap solution.

Do not check for gas leaks with an open flame.

- ☑ Check electrical connections to gas valve.
- Check thermocouple, pilots, flame sensors, ignition cables, etc. for cleanliness and tightness of connections.

AIR MOVERS

- Lubricate motor bearings if they are not the permanently lubricated type.
- With the power turned off, check to see that the motor shalt turns freely and does not bind. This can be done by rotating the fan or blower wheel by hand.
- Inspect the fan or blower wheel to make sure they are not damaged or binding.
- Check to make certain fan is not loose on motor shaft.
 If blower units are used, make certain the blower and motor pulleys are secure.
- On blower units, check for proper belt tension and also look for signs of belt wear.
- Check power connections to motor to ensure they are secure and have not vibrated loose over the past heating sessons.

Note: Equipment using belt drives should have the belt tension checked on initial start-up. Periodic inspection should be made during the heating season to ensure continued proper operation.

CONDENSATE REMOVAL & DISPOS. SYSTEMS

If the units are gas-fired condensing units, check the following items:

- Make sure the condensate lines are clear of obstructions and free flowing.
- Assure the condensate drain line "P" trap has been primed and filled with water.
- Check the condensate overflow switch to make sure it is working properly.
- If the unit(s) has been provided with a condensate removal pump, check to make sure the pump is working properly and has not been damaged.

THERMOSTATS

Check for general cleanliness.

- Check wiring to and from thermostat.
- Check thermostat for proper temperature setting

GREENHOUSE MAINTENANCE TIPS IDENTIFYING POTENTIAL ISSUES









Recognizing Old, Worn or Damaged Units

- Rusted Heat Exchangers
- Cracked Heat Exchangers or Headers

Why is This Bad?

- Unit Heater Efficiency is Reduced
- Harmful Flue Products are Likely Spilling Into the Greenhouse
 - Carbon Monoxide (Human Health Risk)
 - Ethylene (Crop Health Risk)

GREENHOUSE MAINTENANCE TIPS WHEN TO REPLACE A UNIT HEATER – HEAT EXCHANGER





Heat Exchangers are the Most Expensive Component to Replace

- May be Over Half the Cost of a Complete Unit
- Similar to Replacing an Engine on an Old Car

Replacing the complete unit is significantly less expensive than replacing the heat exchanger.

Stainless steel heat exchanger warranty on a new unit is 10 yrs.

Warranty on a replacement heat exchanger is 6 months.


After all the cost, labor & warranty risks of a heat exchanger replacement, the grower still has an old, inefficient unit heater.



HIERARCHY OF HEATING SYSTEM DESIGN







Safety

 Don't Risk People, Crops or Property

Reliability

Avoid No-Heat Situations

Productivity & Comfort

- Healthy & Productive Crops
- Healthy & Productive Occupants

Efficiency

Minimize Operating Costs

WHY USE GAS-FIRED UNIT HEATERS?





Risk Avoidance

Multiple units provide redundancy & avoids no-heat situations

Warm, Forced-Air Heat is Healthy For Plants

- Mitigates condensation & still-air conditions favored by microbial growth & disease
- Moving air helps plants absorb CO₂ more efficiently

Zone Control

- Units only run where heat is needed
- "Off" is the highest efficiency

Harmful Flue Products are Vented Outside

Carbon Monoxide, Water Vapor, Ethylene, etc.

Relatively Low Up-Front & Life-Cycle Cost

- Lots of heat & fan power in a small box
- Relatively easy to install & service

GAS-FIRED UNIT HEATER TYPES











Gravity Vented Unit Heaters – Still Out There!

- 65 68% Thermal Efficiency
- Vertical Venting Only
- Significant Heat-Loss Through Open Draft Diverter
- Rendered Obsolete by EPA 2008

Power Vented Unit Heaters

- 82% Thermal Efficiency
- Motorized Power Exhauster Vents Flue Products Vertically or Horizontally

Separated Combustion Unit Heaters

- 82% Thermal Efficiency
- 2-Pipe Vent System Provides Clean, Dry Outside Air for Combustion
- Heat Exchanger & Burners Protected from High Humidity & Corrosive Chemical Vapors

POWER VENTED UNITS - PTP





Robust Greenhouse Design at a Value Price

18 Gauge Stainless Steel Bent Tube Heat Exchangers... STANDARD!

 Low-cost 10-year warranty protection in high-humidity conditions common in greenhouses

Only 6% Price Premium Over Aluminized PDP

Lowest-Cost S.S. Heat Exchanger Unit on the Market

Totally Enclosed Fan Motor Standard

Controls & Wiring Inside Cabinet for Protection from Airborne Debris

Low-Profile Design from 150 to 400 MBH

For Lower Mounting Heights Found in Greenhouses




HIGH EFFICIENCY UNIT HEATERS









93% - 97% Thermal Efficiency

- 43% Fuel Savings Over Gravity Vented
- 16% Fuel Savings Over Power Vented & Separated Combustion
- Most Natural Gas Utilities Offer Rebates for Furnaces Over 90% Efficiency

Separated Combustion Design

- Provides Clean, Dry Outside Air for Combustion
- Protects Components from Corrosive Effects of High-Humidity & Chemical Vapors Inside

Low Flue Temperatures

Allows Venting with PVC Vent Pipe

BLOWER UNIT HEATERS





Up to 0.7" External Static Pressure

Ductwork & Nozzles Acceptable

- Good for Inlet Ducting Ventilation Air, or Discharge Ducting of Heated Supply Air
- Polytubes Used with Transitions
 - HAF fans now more the norm

Quieter Than Propeller Units

Higher Cost Than Propeller Units

Power Vented

HDB/BDP-Series


Separated Combustion

HDC/BTS-Series

Separated Combustion High-Efficiency

BTC-Series Effinity





OTHER UNIT HEATER TYPES











Hot Water Unit Heaters

- New "Lodronic" Unit
- For use with gas, oil or bio-fuel boiler systems
- Air circulation & snow-load protection along with in-floor/under-bench radiant tube heat

Electric Unit Heaters

- Highest operating cost
- Only recommended for temporary heat or freeze protection
- Limited BTU Range

Oil-Fired Unit Heaters

No. 1 or 2 fuel oil only (no waste oil!)





WHO IS THE COMPETITION & WHY IS MODINE BETTER?





Several Manufacturers of GFUH's

- Reznor (Made in Mexico)
- Sterling (Trane, Dayton, Beacon Morris)
- Lennox (ADP)
- Other Very Limited Mfg's.
 - Residential Sizes Only
 - Some made in China

None Support the Greenhouse Market, but is a Priority with Modine

- Modine supports every national, regional and local show & attends association meetings (NGMA)
 - Modine is available to our customers!

Full Size Range with every type of GFUH

- PTC 10 sizes, BTC 3 Sizes
- No one else has any 93% + blower units
- Low profile designs
- Both clam shell and tubular products available

Modine & It's Representatives are Experts in Greenhouse Heating

- Raley Bros., Walter's Climate, MJM, SWK,
 Emerson Swan & Cornerstone to name a few
- Routinely visits grower operations to lend technical/service/layout support.
- · Works closely with the GH Distributors
- 14 Modine technical service people in the field to handle service issues

Modine Market Leader with Stock Position & Lead Times

- Up to 15,000 units in BV inventory to start the season
- In-stock products ship in 1-2 days
- Non-stock & "specials" normally 2-3 weeks
- 2.5 week production cycle at the plant

WHY IS MODINE BETTER THAN THE COMPETITION?





Thickest Gauge Heat Exchangers & Skin Parts in the Industry

• 18-20 Gauge, competition at 22

Electrostatically Applied Powder Based Paint

- Withstands 500 hours of salt spray testing
- Skin parts individually painted

Totally Enclosed Motors Standard Rotatable Wheel Type Power Venters (PDP/BDP)

One Motor on Every Size Unit

 Some competitors must go to two on the larger sizes to provide adequate air flow across heat exchanger

Literature Dedicated to the Greenhosue Market

- Examples in your folders
- Payback calculation sheet
 - Supports PTC/BTC products
- On-line support information dedicated to greenhouse heating




AIR DISTRIBUTION: INDIVIDUAL GREENHOUSE





In general, have each fan or unit support the horizontal air stream of the others to produce a "flywheel" effect of circulatory air movement around the perimeter.




Air Distribution: Gutter Connected Houses





In general, have each unit heater support the horizontal air stream of the others to produce a "flywheel" effect of circulatory air movement around the perimeter.





EFFICIENCY INCENTIVE PROGRAMS





Efficiency Incentive Program Searches by State, Technology, etc.

Pass Along to Target Customers

- Programs may help offset costs to upgrade to high efficiency equipment
- May find incentives for other energy efficiency upgrades
- Constantly changing programs & legislation will continue to provide opportunities
- PTC/BTC Payback Calculator

www.dsireusa.org



OTHER TIPS FOR ENERGY SAVINGS







Growers With Both Full & Part-Year Greenhouses

- Replace gravity vented units in part-year houses with power vented units from full-year houses.
 - 20% Fuel Savings Over Gravity Vented
- Replace the power vented units from the full-year houses with Effinity units.
 - 19% Fuel Savings Over Power Vented

In this scenario, for each Effinity purchased, the grower achieves significant fuel savings in 2 different greenhouses.

OTHER TIPS FOR ENERGY SAVINGS







Staging Temperature Settings

- Many growers replace individual units as-needed rather than all of them at once.
- This results in a mix of old & new units with different efficiencies in the same space.
- Assuming the grower wants to maintain temperatures between 65° & 70° F
 - Set the old less-efficient units @ 65° F
 - Set the new more-efficient units @ 70° F

In this scenario, the more-efficient units have increased burner hours, and the less-efficient unit heaters have decreased burner hours.







Don't Go it Alone, Utilize the Best Brains of...

- Trade Organizations (NGMA, OFA, ASHRAE, etc.)
- Manufacturers, Reps & Distributors

Know Your Operation

Plant Types, Occupants, Seasonality & Cost Priorities





Use Only Agency-Certified Equipment

CSA, ETL, UL, etc. to ANSI Codes

Use Only Qualified Installers & Service Technicians

- State Licensed and/or Otherwise Experienced
- Pay Them Now or Pay Them Later
- Greenhouse service issues large percentage of our tech calls
- Routinely work directly with growers on service problems

Read & Follow Manufacturers' Instructions

Installation, Operation & Maintenance Instructions





Adhere to Codes

- Building, Safety, Fire & Environmental
- National (IBC, ANSI, OSHA, EPA), State, Local & Insurance

Inspect & Repair Your Systems Before You Need It

Test-Drive it Before the First Cold Front

Use Stainless Steel or Separated Combustion Furnaces


Protects Heat Exchangers & Burners from Humidity

Turn Equipment Off While Chemicals are Being Applied









www.modinehvac.com

THE NEXT LEAP FORWARD





Question: What is Modine's breakthrough solution to the issues of greenhouse heating?

Answer: Modine's <u>NEW</u> Effinity with Conservicore™ Technology


PTC-Series 93% Thermal Efficient Condensing Gas-Fired Unit Heater



EFFINITY DESIGN FEATURES







The Heart and Soul...

Secondary Heat Exchanger Made With AL29-4C Stainless Steel Material

Most Robust Material Available to Withstand Slightly Acidic Condensate

In Effect a Marriage of:

Modine's PTS Separated Combustion line which has been in production for 13 years

&

Trane Company's Residential 90+


AL29-4C Stainless Secondary Heat Exchanger that Modine has been making since 1986

EFFINITY DESIGN FEATURES






Unit Components



EFFINITY DESIGN FEATURES









Separated Combustion

- Protects Heat Exchangers & Components from High Humidity & Chemical Corrosives
- Reduces Greenhouse Heat Loss by 2%

PVC Power Exhauster Wheel & Vent Pipe

Flue Temperatures Only 125° F

Factory Installed External Junction Box Standard

- Disconnect Switch
- Convenience Outlet
- Terminal Board
- Indicator Lights
- Factory installed BMS compatible control

PTC-SERIES CONDENSING UNIT HEATERS





PTC Outputs Closely Match Outputs of Standard Efficiency Units_for Ease of Comparison When Sizing & Selecting New Construction, Expansion or Replacement Jobs

PTC 55	82% 45MBH unit
PTC 65	82% 60MBH unit
PTC 85	82% 75MBH unit
PTC 110	82% 100MBH unit
PTC 135	82% 175MBH unit
PTC 155	82% 175MBH unit
PTC 180	82% 200MBH unit
PTC 215	82% 250MBH unit
PTC 260	82% 300MBH unit
PTC 310	82% 350MBH unit

Condensate Production

Approx. 1+ Gallons / running hour for Small Units Approx. 2+ Gallons / running hour for Large Units

Slightly Acidic – Like Soda (Pop)
Need to Drain Both Unit & Vent System

CONDENSATE REMOVAL







Condensate Pumped Into Flex Hose Up to Ceiling & Pitched Down to Nearest Floor Drain Across Room

Condensate Drains for Cabinet & Flue Vent

Condensate Pump & Mounting Kit

Approximately ½ – 2 Gallons/Hr. Slightly Acidic (pH ~4.5)

EFFINITY APPLICATION FLEXIBILITY





409 Stainless Steel Primary Heat Exchangers

Recommended for Greenhouse Applications Due to Humidity

- To Gain 10 year Warranty on Primary Heat Exchanger
- Secondary Heat Exchanger AL29-4C is always 10yr

Finger-Proof (OSHA) Fan Guards

For Installations with bottom of unit at 7ft.

2-Point Suspension Kits


Concentric Vent Kits

Condensate Pumps & Neutralizer Kits

Deflector Hoods & Vertical Deflector Blades

Energy Saver Kit (Part of BMS Control)

Ceiling T-Stat Energizes Fan Without Burner as Ceiling Temps Rises







Return to Ma	in Menu 👛 Prii	nt Menu	Save As Menu				
Effinity 93	back Calculator	V2.50	APPLIED IN	DINE ERMAL INNOVATION*			
JOB II	NFORMATION		ENERGY / FINANCIA	L / ENVIROI	NMENTAL AN	ALYSIS	
Project Name: Dubuque Greenho Submitted By: FarmTek State: Iowa OPERATII		9/16/13 AP	Note: If using gas pricing in \$1100 Heater Model Number: Heater Input Rating (each): Heater Thermal Efficiency (%):	ost per Therm: 0 ft ³ , divide by 10.5 to Option 1	\$0.830	Click for Avg U.S. Gas Prices	
MONTHS OF OPERATION:	OCCUPIED HOURS OF OPERAT	IION:	Heater Quantity:	1	1		
Sep Sep			Annual Therms Consumed: Annual Fuel Consumption Cost: Potential Annual Heater Equipment Cost (each): Energy Efficiency Rebate (if app Total Heater Equipment Cost Total Equipment Cos Simple Breakeve 5-Ye 5-Year Retur	\$0 blicable, each): \$0 t Premium for n Years on ar Gain On	\$3,290 \$325 \$2,965 or Effinity ⁹³ : Investment:	\$1,590 \$2,965 1.86 \$4,986 168.2%	
CALCULATED HEATING D	EGREE DAYS, HEATING H	OURS*	The use of the Effinity93	in this analy	sis is the eq	uivalent of:	
			/ LAC /		oided (lbs):	21,074	
Heating Degree Days:		Total 6715	# of Cars Ri Urban Trees Plant		m the Road:	1.8 245	
Heating Hours:		2585	# of Average Ho			3.7	
Heavy red areas	*Based on average climate data. indicate fields that are user entered	data.	Disclaimer: Actual realized savings including, but not limited to, changing use or construction, etc.				

Need to Know:

- Location of GH
- Month's of Operation
- Occupied Hours
- Indoor Design Temp
- Heat Loss
- Fuel Cost per therm
- 65% or 80% unit to compare with





🕱 72-910 - Effinity93 Payback Calculator-Greenhouse [Compatibility Mode] - Microsoft Excel							
Return to Main Menu Print Menu	Save As Menu						
Efficity 93 Energy Savings - Pay	APPLIED THERMAL INNOVATION						
JOB INFORMATION	ENERGY / FINANCIAL / ENVIRONMENTAL ANALYSIS						
Project Name: Dubuque Greenhouse Submitted By: FarmTek Date: 09/16/13 State: Iowa City: Dubuque Regional AP	Building Design Heat Loss (Btu/hr): 160,000 Fuel Cost per Therm: 50.830 Note: If using gas pricing in \$1000 nt, divide by 10.5 to get approx \$therm. Option 1 Effinity 53 Heater Model Number: PD200 PTC180						
OPERATING PERIOD DATA	Heater Input Rating (each): 200,000 180,000						
OFERATING FERIOD DATA	Heater Quantity: 1 1						
MONTHS OF OPERATION: OCCUPIED HOURS OF OPERATION:	Annual Therms Consumed: Annual Fuel Consumption Cost: S5.282 \$3.691						
CALCULATED HEATING DEGREE DAYS, HEATING HOURS*	The use of the Effinity93 in this analysis is the equivalent of:						
Occurried Hassenwied Total	# of Cars Removed from the Road: 1.8						
Occupied Unoccupied Total Heating Degree Days: 6715 0 6715	# of Cars Removed from the Road: 1.8 Urban Trees Planted/Grown for 10 Years: 245						
Heating Hours: 2585 0 2585	# of Average Homes Gas Consumption: 3.7						
*Based on average climate data.							
Heavy red areas indicate fields that are user entered data.	Disclaimer: Actual realized savings can vary significantly based on a number of factors, including, but not limited to, changing fuel prices, changes in climate, changes in building use or construction, etc.						

What it will give you:

- Annual Fuel Savings per Unit
- Simple Breakeven Years on Investment
- 5 Year Gain on Investment
- 5 Year Return on Investment (ROI)





Simple Breakeven Years on Investment

 Amount of time cost difference to purchase higher efficiency will be recouped with the energy savings.

5 Year Gain on Investment

• Annual Savings (x5) minus initial investment.

5 Year ROI

(5 yr net gain / net investment) x 100

ASHRAE – American Society of Heating, Refrigeration, and Air Conditioning Engineers





Let's Look at Some Real World Examples





					Simple	5 Yr. Gain	5 Yr.
Address	City	St	Zip	Cost/Gal	Breakeven (Yrs.)	on Investment	ROI
896 Bonnie Plant Rd	Union Springs	AL	36089	\$1.43	2.66	\$1,131	88%
10693 Hwy 76	Pala	CA	92059	\$1.79	4.4	\$174	14%
42678 Weld Cr 35	Pierce	CO	80650	\$1.78	0.69	\$8,057	627%
1276 Center Street	Waverly	FL	33877	\$1.76	9.01	(\$512)	-45%
1700 Co Hwy 13	New Berlin	NY	13411	\$1.76	0.77	\$7,088	551%
21109 Cotton Slash Rd	Marysville	OH	43040	\$1.34	1.18	\$4,166	324%
10639 Plowden Mill Rd	Alcolu	SC	29001	\$1.69	2	\$1,937	151%
8903 West Side Hwy	Castle Rock	WA	98611	\$1.73	1.05	\$4,862	378%

